

Be

# MATERIAL SAFETY DATA SHEET

## NFPA RATINGS

"BLANK" spaces are not permitted. - If needed to complete all spaces, use the code system shown below.

NA (Not applicable)	NE (Not established)	NDA (No data available)	NK (None known)	NONE (None)	NR (Not Required)
------------------------	-------------------------	----------------------------	--------------------	----------------	----------------------

HEALTH	2
FIRE	4
REACTIVITY	0
SPECIAL	NA

**QUICK IDENTIFIER**  
(Product name as it appears on label or package) **BELT DRESSING** FEB 26 2001

**PART NUMBER(S)** 765-1397 (13.75oz. Aerosol)  
(As it or they appear on label or package)

SUPPLIER TO NAPA OF THE PRODUCT SHOWN ABOVE			
Company Name	Balkamp, Incorporated	PHONE	(317) 244-7241
Street Address	2601 S. Holt Road	EMERGENCY	1-800-424-9300
	P.O. Box 418277	CONTACT(24HRS)	(CHEMTREC)
City, State, Zip	Indianapolis, IN 46241	DATE MSDS WAS PREPARED	3/24/92
		FAX NO.	(317) 244-2644

MANUFACTURER (or supplier) FROM WHOM BALKAMP PURCHASES THE ABOVE NAMED PRODUCTS	
Company Name	Spcayon Products
Street Address	26300 Fargo Ave.
	Bedford Heights, OH 44146
City, State, Zip	
	Phone: (216) 292-7400
	Emergency Contact: (Optional)

### SECTION ONE: HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Show all health or physical hazards which comprise 1% or greater of the composition, and all carcinogens if 0.1% or greater of the composition. Do not show a common name or synonym unless it is shown in parentheses immediately following or below the technical name)

TECHNICAL (specific) CHEMICAL NAME	C.A.S. NO.	OSHA PEL	ACGIH TWA (TLV)	Other Limits Recommended (Optional)	% Content
1,1,1-Trichloroethane*	71-55-6	350 ppm	350 ppm		
Heptane	142-82-5	500 ppm	400 ppm		
Petroleum Hydrocarbon Mixture	NE	5mg/m <sup>3</sup>	5mg/m <sup>3</sup>		
Hydrocarbon Resin	64742-16-1	5mg/m <sup>3</sup>	5mg/m <sup>3</sup>		
Resin	63393-89-5	NE	NE		
Propane	74-98-6	1000 ppm	1000 ppm		
Isobutane	75-28-5	1000 ppm	1000 ppm		

\* This is subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986, and 40 CFR, Part 372.

### SECTION TWO: FIRE AND EXPLOSION DATA

FLASH POINT (Show testing method used): -40°F (TCC)	FLAMMABLE LIMITS	LEL	1.8	UEL	12.0
EXTINGUISHING MEDIA: Water Fog, Dry Chemical, Carbon Dioxide					
SPECIAL FIRE FIGHTING PROCEDURES: NK					
UNUSUAL FIRE & EXPLOSION HAZARDS: Cans may burst when heated.					

HAZARDOUS PRODUCTS FORMED BY FIRE OR THERMAL DECOMPOSITION: Carbon Dioxide, Halogen Acids, Phosgene

### SECTION THREE: PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT	-40°F to unknown	SPECIFIC GRAVITY (H <sub>2</sub> O=1)	0.9	MELTING POINT	NA	VAPOR PRESSURE (mmHg.)	45 @ 75°F	VAPOR DENSITY (Air=1)	4.0	% VOLATILE BY VOLUME	NK
EVAPORATION RATE (ButylAcetate=1)	<3		SOLUBILITY IN WATER	Nil		APPEARANCE & ODOR					

### SECTION FOUR: REACTIVITY AND STABILITY DATA

STABLE	UNSTABLE	<input checked="" type="checkbox"/> CONDITIONS TO AVOID		High temperatures	
HAZARDOUS POLYMERIZATION	MAY OCCUR	WILL NOT OCCUR	<input checked="" type="checkbox"/> CONDITIONS TO AVOID		NK
INCOMPATIBILITY (Materials to avoid)	Strong oxidizers				
HAZARDOUS "NON-THERMAL" OR "NON-FIRE" DECOMPOSITION OR BY-PRODUCTS:	NK				

SECTION FIVE: HEALTH HAZARD DATA

HEALTH HAZARDS - ACUTE  CHRONIC  NOTE: If a CHRONIC over-exposure hazard is present, elaborate below as to what the effects are, or possibly could be long term exposure to vapor may cause lung, liver, or kidney damage. Long term exposure to the solvents listed have been reported to affect the central nervous system.

ROUTES OF ENTRY	MANNER	YES	NO	-SIGNS AND SYMPTOMS OF AN ACUTE OVER-EXPOSURE OR CONTACT-
	INHALATION	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Difficulty in breathing. High vapor concentrations may cause narcosis or dizziness.
	SKIN	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Redness. Prolonged or repeated contact can cause de-fatting of skin.
	INGESTION	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Vomiting
	EYES	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Irritation

EMERGENCY AND FIRST-AID PROCEDURES	INHALATION	Remove to fresh air. Give artificial respiration if breathing has stopped. Administer oxygen if breathing remains difficult.
	SKIN	Wash with soap and water.
	INGESTION	Do not induce vomiting. Get Medical attention.
	EYES	Flush with water for 15 minutes. Call physician if irritation persists

Medical conditions generally aggravated by exposure, or NOTE TO PHYSICIAN: Pre-existing heart or respiratory disorders.

Does this product contain a chemical or chemicals known to be a carcinogen by: NTP?  IARC MONOGRAPHS?  OSHA?  If yes; list the chemical(s).

SECTION SIX: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to take in case the material is spilled or released: Pick up with an absorbent and put in a metal closed container.

Disposal Method: In accordance with all applicable Federal, State, and local regulations.

Precautions to take in Storage & Handling: Keep away from heat, sparks, or open flame.  
Store below 120°F.

SECTION SEVEN: CONTROL MEASURES

Respiratory Protection: (Specify Type) If TLV is exceeded, wear a SCBA. GLOVES None normally required  
Ventilation: LOCAL? Yes MECHANICAL? NR  
OTHER: Don't smoke while using. Wash hands after using. EYE PROTECTION? Safety goggles recommended

SECTION EIGHT: TRANSPORTATION DATA

Description: CONSUMER COMMODITY	Domestic Air	Description:
Hazard Class: ORM-D		Hazard Class:
I.D. No.:		I.D. No.:
Label Required:		Label Required:

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief, but is not guaranteed to be so. Nothing herein is to be understood as a recommendation in favor of any practice or any product in violation of any patent, law, or regulation. It is the user's responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using this MSDS, and since conditions of use are not under our control, we must necessarily disclaim all liability with respect to the use of a Material Safety Data Sheet supplied by us.