

DENNISON STATIONERY PRODUCTS COMPANY -- CARTER'S RUBBER CEMENT -- 8040-00-262-9040

===== Product Identification =====

Product ID:CARTER'S RUBBER CEMENT
MSDS Date:07/19/1988
FSC:8040
NIIN:00-262-9040
MSDS Number: BHDFB
=== Responsible Party ===
Company Name:DENNISON STATIONERY PRODUCTS COMPANY
Address:300 HOWARD STREET
City:FRAMINGHAM
State:MA
ZIP:01701
Country:US
Emergency Phone Num:508-879-0511 X4636
CAGE:HO918

=== Contractor Identification ===
Company Name:DENNISON STATIONARY PRODUCTS CO
Address:300 HOWARD STREET
Box:City:FARMINGTON
State:MA
ZIP:01701
Country:US
Phone:508-879-0511
CAGE:HO918

===== Composition/Information on Ingredients =====

Ingred Name:SOLVENT NAPHTHA
CAS:67472-89-8
Fraction by Wt: 88.6%
Other REC Limits:400 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:OVEREXPOSURE CAN LEAD TO CENTRAL
NERVOUS SYSTEM DEPRESSION PRODUCING HEADACHES, DIZZINESS, NAUSEA,
AND LOSS OF CONSCIOUSNESS.
Effects of Overexposure:HEADACHES, DIZZINESS, NAUSEA, LOSS OF
CONSCIOUSNESS.
Medical Cond Aggravated by Exposure:SKIN DISEASE, CHRONIC RESPIRATORY
DISEASE

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER, CALL PHYSICIAN. INHALATION: REMOVE TO
FRESH AIR. RESTORE BREATHING. CALL PHYSICIAN. SKIN: WASH WITH SOAP
AND WATER. LAUNDRER CLOTHING. IF IRRITATION PERSISTS, GET MEDICAL
ATTENTION. INGESTION: DO NOT INDUCE VOMITING, GET IMMEDIATE MEDICAL
ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:< 10F/-24C

Lower Limits:7.0

Upper Limits:1.1

Extinguishing Media:CO2, FOAM, DRY CHEMICAL, WATER FOG OR SPRAY

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING INCLUDING NIOSH
SELF-CONTAINED BREATHING APPARATUS COOL EXPOSED CONTAINERS WITH
WATER SPRAY.

Unusual Fire/Explosion Hazard:IN CASE OF LARGE FIRES, ALSO COOL
SURROUNDING EQUIPMENT AND STRUCTURES WITH WATER. DO NOT MIX
WITH STRONG OXIDANTS.

===== Accidental Release Measures =====

Spill Release Procedures:AVOID OPEN FLAMES OR SPARK SOURCES. PROVIDE
ADEQUATE VENTILATION. ADD ABSORBANT (SAWDUST, SAND ETC.) TO SPILL
AREA. TO AVOID SPILLING, DEEP CAP TIGHTLY CLOSED WHEN NOT USING.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID OPEN FLAMES, SPARK SOURCES,
SPLASH SPILLING, EXCESSIVE HEAT. KEEP CONTAINERS CLOSED WHEN NOT
USING.

Other Precautions:CAREFULLY READ ALL DIRECTIONS AND CAUTIONS ON PRODUCT
CONTAINER.

===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL EXHAUST IF NEEDED TO CONTROL VAPOR. MECHANICAL (GEN)
VENTILATION EXPLOSION PROOF EQUIPMENT.

Protective Gloves:PVA OR NITRILE RUBBER

Eye Protection:SAFETY GLASSES/GOGGLES

Work Hygienic Practices:WASH HANDS BEFORE EATING, DO NOT SMOKE OR USE
NEAR OPEN FLAME.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:151 - 225F

Vapor Pres:250 @ 100F

Vapor Density:3.3

Spec Gravity:.72

Evaporation Rate & Reference:5.8 (BUTYL ACETATE = 1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BUFF COLOR LIQUID WITH HYDROCARBON ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDANTS LIKE CHLORINE

Stability Condition to Avoid:HEAT, SPARKS, AND OPEN FLAMES

Hazardous Decomposition Products:CARBON MONOXIDE AND UNIDENTIFIED
ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:EVAPORATE AND PEEL RESIDUE FROM SURFACE. TREAT
AS HYDROCARBON.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.