8	ECTIO	N 1	_	CHE	MIC	CAL	P	RODI	JCT	AN) C	MPAN	ΙΥ	I DENT	IFIC	ATION
CHEMICAL PRODUCT II PRODUCT CONTRACT NAME FORMULA II MSDS PREPARAMANUFACTURE	D . LASS E . D . ATION	DA	·	• •	•	•	•	. : . : . :	PACE 13	INT RYL: 8-2:	. W# [C E 50B	EPOXY	B/	ASE GLOSS	CAT	ALYST (PART B)
NAME ADDRESS .			•			•	•	. :	CO1	RONZ 8 OZ	ADO	PAIN COUNT	TI Y	CO. ROAD		
TELEPHONE EMERGENCY EMERGENCY	CONT TELE	ACT PHO	NE		•		•	. : . :	ED: 38: CHI	GEW: 6-4; EMT: 00)	ATE: 28-6 REC 424	3 461 1-930	00			32132
	SECT	ION	2	- C	OMI	PQ\$	ΙT	ION.	/IN	FORI	TAN	ON C	N	HAZAR	DOUS	INGREDIENTS
Material Sa:	fety r saf	Data e ha ***	a S and	hee lin	t 0	con	ta. al. **	ins l in	in:	form	nati	on c	n ide	good :	indu:	ts. This strial
POTENTIAL HI EYES: Pri SKIN: May INHALATION	EALTH imary y irr N: W	EFI iri itat ith	FEC	TS ant ski	n. ver		lai	tion		vapo	or c	or sp	ra	y mist	t may	y irritate 9 & nausea
ROUTE(S) OF Exposus conditions of	re ma	y be		nha	lat	:10	n a	and,	or/	ski	n c	r ey	e	contac	- - -	
conditions (or us	€.												•••••	26, (depending on
CARCINOGENIC No ingrearcinogen.	CITY		Ln	thi	s ŗ	oro	du	ct i	ls (an 1	ARC	, NT				•
CARCINOGENIC No ing	CITY redie	nt i		thi	s ŗ	oro	du						P	or OSI	4A 1:	isted
CARCINOGENIC No ingr carcinogen. CHRONIC EFFE	CITY redie	nt i							FIRS	 8T #		 MEAS	P UR	or OS!	4A 1:	•

EMERGENCY FIRST AID:

EYE CONTACT: Flush at once with large amounts of lukewarm water for at least 15 minutes and get medical attention.

CORONADO PAINT CO. MATERIAL SAFETY DATA SHEET

138-250B

1

SKIN CONTACT: Remove from skin with soap and water. Remove drenched clothing. If irritation persists, consult a physician.

INHALATION: If affected by inhalation of vapor or spray mist, remove to

fresh air. If necessary, restore breathing; in this case

contact physician at once.

INGESTION: If victim is conscious, give 2 glasses of water to dilute.

Do not induce vomiting. Consult physician or poison control

center at once.

NOTE TO PHYSICIAN:

Not Applicable.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE CHEMICAL:

Flammability Classification : N/A

Flashpoint N/A

High - -N/A

EXTINGUISHING MEDIA

Use extinguishing media appropriate for surrounding fire. After water evaporates, remaining material will burn; use CO2, dry chemical or foam (National Fire Protection Association Class B extinguisher).

FIRE-FIGHTING PROCEDURES AND EQUIPMENT

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode when exposed to extreme heat; use water spray to cool. Product in open containers may spatter when the temperature exceeds boiling point of water.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Ventilate as described in Section 8. Avoid unnecessary skin contact. Stop and/or contain spill if it can be done safely. Avoid discharge into drains, sewers or waterways.

CLEAN-UP

Collect by absorption, shovel and/or wet moping.

CORONADO PAINT CO. MATERIAL SAFETY DATA SHEET

138-250B

SECTION 7 - HANDLING AND STORAGE

HANDLING

Transfer only to approved containers with complete & appropriate labeling. Do not take internally. Keep out of the reach of children.

STORAGE

Do not store above 120 Degrees F. Close container after each use.

SPECIAL COMMENTS

Do not take internally. Wash with soap and water before eating, drinking, smoking or using toilet. Avoid FREEZING this product.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to chemicals in Section 2 is maintained below applicable exposure limits.

RESPIRATORY PROTECTION

Where exposures are below the PEL, no respiratory protection is required. Where exposures exceed the PEL, use a respirator approved by NIOSH or a full protective suit with air supply appropriate for the chemical(s) and level of exposure.

EYE PROTECTION

Wear safety spectacles with unperforated side shields

PROTECTIVE GLOVES

None required for normal application of limited duration is expected. For long or repeated contact, wear chemical resistant gloves.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Vapor Density	: 17mmHg@ 68 Degrees F (water) :: LIQUID	
Specific Gravity	.: 8.8938 LB/GL .: .063 .: .000 n-Butyl Acetate = 1)	

CORONADO PAINT CO. MATERIAL SAFETY DATA SHEET

138-250B SECTION 10 - STABILITY AND REACTIVITY STABILITY This product is stable INCOMPATIBILITIES (Materials to Avoid) None known. HAZARDOUS POLYMERIZATION Will not occur. CONDITIONS TO AVOID High temperatures. HAZARDOUS PRODUCTS OF DECOMPOSITION Heating to decomposition, as in a fire or welding, may produce hazardous fumes. Fumes may contain carbon monoxide, carbon dioxide and oxides of nitrogen. SECTION 11 - TOXICOLOGICAL INFORMATION No data at this time. SECTION 12 - ECOLOGICAL INFORMATION No data at this time. SECTION 13 - DISPOSAL CONSIDERATIONS WASTE DISPOSAL Dispose of this product in accordance with applicable local, county, state and federal regulations, by incinerating, or treating and disposing in approved facility. Do not incinerate closed containers. SECTION 14 - TRANSPORT INFORMATION DOT SHIPPING NAME : PAINT DOT PLACARD NONE

CORONADO PAINT CO.

138-250B

MATERIAL SAFETY DATA SHEET

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA Regulations.

SARA 313 TOXIC CHEMICALS:

This product contains NONE of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

SECTION 16 - OTHER INFORMATION

MSDS Prepared for .

MSDS Last Prepared NONE
HMIS Rating: Health- 2 Flammability- 1
Reactivity- 0

This Material Safety Data Sheet conforms to the Hazard Communication Standard, 29 CFR 1910.1200(g)(4).

The above information pertains to this product as currently formulated and is based on the information available, as of this date. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Abbreviations used: int. - interior; ext. - exterior; MSDS - Material Safety Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA -Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable IARC - International Agency for Research on Cancer; NE - Not established

CORONADO PAINT CO. MATERIAL SAFETY DATA SHEET

138-250B

NTP - National Toxicological Program; CFR - Code of Federal Regulations; OSHA - Z 29CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC - Tag Closed Cup; LEL - Lower Explosive Limit; Mg/m3 or Mg/Cu M - milligram per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts per million; NIOSH - National Institute of Occupational Safety and Health; MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.