

-----  
SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION  
-----

CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT ID . . . . . : 138-38A  
PRODUCT CLASS . . . . . : PAINT, WATER BASE  
TRADE NAME . . . . . : ACRYLIC EPOXY- DEEP BASE (PART A)  
FORMULA ID . . . . . : 138-38A  
MSDS PREPARATION DATE . . . . . : 01/23/2003

MANUFACTURER IDENTIFICATION:

NAME . . . . . : CORONADO PAINT CO.  
ADDRESS . . . . . : 308 OLD COUNTY ROAD

EDGEWATER FL 32132  
TELEPHONE . . . . . : 386-428-6461  
EMERGENCY CONTACT . . . . . : CHEMTREC  
EMERGENCY TELEPHONE . . . . . : (800) 424-9300

-----  
SECTION 2 - COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS  
-----

1

CAS# 112-34-5  
DIETHYLENE GLYCOL MONOBUTYL ETHER  
PCT BY WT: 3.7680 VAPOR PRESSURE: .020 MMHG @ 68F  
EXPOSURE LIMIT:  
LD50: Oral (Rat)- 7292 mg/kg

2

CAS# 111-77-3  
DIETHYLENE GLYCOL m-METHYL ETHER  
PCT BY WT: 3.5870 VAPOR PRESSURE: .100 MMHG @ 68F  
EXPOSURE LIMIT:  
ACGIH TLV/TWA: NE  
OSHA PEL/TWA: NE  
LD50: Oral (Rat) - 7128 mg/kg  
CA PROPOSITION 65: Yes

3 DIBUTYL PHTHALATE

CAS# 84-74-2  
1,2-BENZENEDICARBOXYLIC ACID, DIBUTYL ESTER  
PCT BY WT: 1.0250  
EXPOSURE LIMIT:  
ACGIH TLV/TWA: 5 mg/cu m - TWA  
OSHA PEL/TWA: 5 mg/cu m - TWA  
LD50: Oral(Rat) 20-25 g/kg

4

CAS# 13463-67-7  
TITANIUM DIOXIDE  
PCT BY WT: 10 - 15  
EXPOSURE LIMIT:  
ACGIH TLV/TWA: 10 mg/cu m (Total Dust) - TWA  
OSHA PEL/TWA: 10 mg/cu m (Total Dust) - TWA  
LD50: Oral (Rat)- >7500 mg/kg (TiO2)

5 HYDROUS KAOLIN

CAS# 1332-58-7

CORONADO PAINT CO.  
MATERIAL SAFETY DATA SHEET

2 mg/cu m - TWA  
10 mg/cu m (Total dust) - TWA

\*\*\*\*\*  
 This product contains one or more Hazardous Air Pollutants.  
 \*\*\*\*\*  
 This product contains no reported carcinogens or suspected carcinogens according to the information provided in Section 3 of this MSDS.  
 \*\*\*\*\*  
 This product contains pigments, which may become a dust nuisance when removed by abrasive blasting, sanding, or grinding.  
 \*\*\*\*\*

SECTION 3 - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYES: Primary irritant.

SKIN: N/A

INHALATION: With poor ventilation, vapor or spray mist may irritate respiratory mucous membranes, causing headache & nausea.

INGESTION: N/A

ROUTE(S) OF EXPOSURE

Exposure may be inhalation and/or skin or eye contact, depending on conditions of use.

CARCINOGENICITY

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

CHRONIC EFFECTS:

None recognized.

SECTION 4 - FIRST AID MEASURES

EMERGENCY FIRST AID:

EYE CONTACT: Flush at once with large amounts of lukewarm water for at least 15 minutes and get medical attention.

SKIN CONTACT: Remove from skin with soap and water. Remove drenched clothing. If irritation persists, consult a physician.

INHALATION: If affected by inhalation of vapor or spray mist, remove to fresh air. If necessary, restore breathing in this case

CORONADO PAINT CO.  
MATERIAL SAFETY DATA SHEET

138-38A

1

-----  
contact physician at once.

INGESTION: If victim is conscious, give 2 glasses of water to dilute.  
Do not induce vomiting. Consult physician or poison control  
center at once.

NOTE TO PHYSICIAN:  
Not Applicable.

-----  
SECTION 5 - FIRE FIGHTING MEASURES  
-----

FIRE AND EXPLOSIVE PROPERTIES OF THE CHEMICAL:

Flammability Classification . . . . .	:	N/A
Flashpoint . . . . .	:	N/A
Explosion Level . . . . .	:	Low - .5
		High - 24.6

EXTINGUISHING MEDIA

Use extinguishing media appropriate for surrounding fire. After water evaporates, remaining material will burn; use CO2, dry chemical or foam (National Fire Protection Association Class B extinguisher).

FIRE-FIGHTING PROCEDURES AND EQUIPMENT

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode when exposed to extreme heat; use water spray to cool. Product in open containers may spatter when the temperature exceeds boiling point of water.

-----  
SECTION 6 - ACCIDENTAL RELEASE MEASURES  
-----

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Ventilate as described in Section 8. Avoid unnecessary skin contact. Stop and/or contain spill if it can be done safely. Avoid discharge into drains, sewers or waterways.

CLEAN-UP

Collect by absorption, shovel and/or wet mopping.

-----  
SECTION 7 - HANDLING AND STORAGE  
-----

HANDLING

Transfer only to approved containers with complete & appropriate labeling. Do not take internally. Keep out of the reach of children.

STORAGE

CORONADO PAINT CO.  
MATERIAL SAFETY DATA SHEET

138-38A

1

Do not store above 120 Degrees F. Close container after each use.

**SPECIAL COMMENTS**

Do not take internally. Wash with soap and water before eating, drinking, smoking or using toilet. Avoid FREEZING this product.

**SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION**

**VENTILATION**

Local exhaust preferable. General exhaust acceptable if the exposure to chemicals in Section 2 is maintained below applicable exposure limits.

**RESPIRATORY PROTECTION**

Where exposures are below the PEL, no respiratory protection is required. Where exposures exceed the PEL, use a respirator approved by NIOSH or a full protective suit with air supply appropriate for the chemical(s) and level of exposure.

**EYE PROTECTION**

Wear safety spectacles with unperforated side shields.

**PROTECTIVE GLOVES**

None required for normal application of limited duration is expected. For long or repeated contact, wear chemical resistant gloves.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Vapor Density . . . . .	:	N/A
Vapor Pressure . . . . .	:	17mmHg@ 68 Degrees F (water)
Physical State . . . . .	:	LIQUID
Boiling Point Range . . . . .	:	Lower - 212.0 °F Higher - 453.0 °F
Specific Gravity . . . . .	:	1.172
Weight per Volume . . . . .	:	9.7561 LB/GL
VOC - Total (lbs./gal) . . . . .	:	1.974
Evaporation Rate . . . . .	:	.020 (n-Butyl Acetate = 1)
Volatile by Weight . . . . .	:	52.8540
Volatile by Volume . . . . .	:	62.0480

**SECTION 10 - STABILITY AND REACTIVITY**

**STABILITY**

This product is stable.

**INCOMPATIBILITIES (Materials to Avoid)**

None known.

CORONADO PAINT CO.  
MATERIAL SAFETY DATA SHEET

138-38A

1

HAZARDOUS POLYMERIZATION  
Will not occur.

CONDITIONS TO AVOID  
High temperatures.

HAZARDOUS PRODUCTS OF DECOMPOSITION  
Heating to decomposition, as in a fire or welding, may produce hazardous fumes. Fumes may contain carbon monoxide, carbon dioxide and oxides of nitrogen.

SECTION 11 - TOXICOLOGICAL INFORMATION

No data at this time.

SECTION 12 - ECOLOGICAL INFORMATION

No data at this time.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Dispose of this product in accordance with applicable local, county, state and federal regulations, by incinerating, or treating and disposing in approved facility. Do not incinerate closed containers.

SECTION 14 - TRANSPORT INFORMATION

DOT HAZARD CLASS . . . . . : N/A  
DOT PACKAGING GROUP . . . . . : N/A  
DOT LABEL . . . . . : NONE  
DOT SHIPPING NAME . . . . . : PAINT  
DOT PLACARD . . . . . : NONE  
UN/NA NUMBER . . . . . : NONE

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA Regulations.

SARA 313 TOXIC CHEMICALS:

This product contains the following substances subject to the

CORONADO PAINT CO.  
MATERIAL SAFETY DATA SHEET  
1

138-38A

reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

DIETHYLENE GLYCOL MONOBUTYL ETHER  
CAS# 112-34-5 PCT BY WT: 3.9680

DIETHYLENE GLYCOL m-METHYL ETHER  
CAS# 111-77-3 PCT BY WT: 3.5870

1,2-BENZENEDICARBOXYLIC ACID, DIBUTYL ESTER  
CAS# 84-74-2 PCT BY WT: 1.0250

SECTION 16 - OTHER INFORMATION

Prepared by . . . . . : LINDA OVERTON  
Date of issue . . . . . : 01/23/2003  
Last Revision Date . . . . . : 08/29/2002

MSDS Prepared for

MSDS Last Prepared . . . . . : NONE  
HMIS Rating: Health- 1 Flammability- 0  
Reactivity- 0

\*\*\*\*\*  
This Material Safety Data Sheet conforms to the Hazard Communication Standard, 29 CFR 1910.1200(g)(4).

The above information pertains to this product as currently formulated and is based on the information available, as of this date. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

\*\*\*\*\*  
Abbreviations used: int.- interior; ext.- exterior; MSDS - Material Safety Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA - Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable; IARC - International Agency for Research on Cancer; NE - Not established; NTP - National Toxicological Program; CFR - Code of Federal Regulations; OSHA - 29CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC -

136-36A

-----  
CORONADO PAINT CO.  
MATERIAL SAFETY DATA SHEET  
1

-----  
Tag Closed Cup: LEL - Lower Explosive Limit; Mg/m<sup>3</sup> or Mg/Cu M - milligram  
per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts  
per million; NIOSH - National Institute of Occupational Safety and Health;  
MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.  
-----