

Material Safety Data Sheet
 May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072



IDENTITY (As Used on Label and List)
DUST DOWN SWEEPING COMPOUND "C"

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name GREENOUGH PAPER CO., INC.	Emergency Telephone Number (413) 786-8944
Address (Number, Street, City, State, and ZIP Code) 14 HEYWOOD AVENUE WEST SPRINGFIELD, MA. 01089	Telephone Number for Information (413) 732-2308
	Date Prepared NOVEMBER 16, 1988
	Signature of Preparer (optional)

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
OIL: LUBRICATING OIL FLEXXON 641	5mg/m³	5mg/m³	LESS THAN 10%	
VE: ATLANTIC MALACHITE GREEN CRYSTALS	N/A	N/A	LESS THAN 1/100 OF 1	
OTHER COMPONENTS: ARE NON-HAZARDOUS				
		10 5		
SILICA LIMITS --- RESPIRABLE DUST = 10mg/m³				
2+SiO₂				

Section III — Physical/Chemical Characteristics

Boiling Point	N/A	Specific Gravity (H₂O = 1)	UNKNOWN
Vapor Pressure (mm Hg.)	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water	INSOLUBLE		
Appearance and Odor	GREEN - SLIGHT LUBE OIL ODOR		

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used) FLASH POINT OF OIL COMPONENT 320°F	Flammable Limits N/A	LEL	UEL
Extinguishing Media	FOAM AND WATER FOG		
Special Fire Fighting Procedures	PROTECT AGAINST THE HAZARDOUS EFFECTS OF THE NORMAL PRODUCTS OF COMBUSTION ON OXYGEN DEFICIENCIES.		
	N/A		

Section V — Reactivity Data

Stability | Unstable | Conditions to Avoid

Stable | X

Compatibility (Materials to Avoid) **OXIDIZING AGENTS**

Byproducts **N/A**

Hazardous Polymerization | May Occur | Conditions to Avoid

Will Not Occur | X

Section VI — Health Hazard Data

Route(s) of Entry: Inhalation? **NO** YES Ingestion? **N/A**

Health Hazards (Acute and Chronic) **SKIN OR EYE IRRITATION**

NTP? **NO** IARC Monographs? **NO** OSHA Regulated? **NO**

Signs and Symptoms of Exposure **OIL OR SAND MAY IRRITATE SKIN.**

Medical Conditions Generally Aggravated by Exposure **OIL OR SAND MAY IRRITATE SKIN.**

Emergency and First Aid Procedures **WASH SKIN WITH SOAP AND PLENTY OF WATER. FOR EYE CONTACT, REMOVE MATERIAL AND FLUSH WITH WATER.**

Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled

SWEEP UP AND DISPOSE IN NORMAL MANNER.

Waste Disposal Method **CONVENTIONAL**

Precautions to Be Taken in Handling and Storing **WHEN LIFTING HEAVY CONTAINERS, LIFT WITH LEGS, NOT BACK. STORE MATERIAL IN DRY AREA AWAY FROM EXCESSIVE HEAT. LESS THAN 150°C**
N/A

Section VIII — Control Measures

Respiratory Protection (Specify Type) **N/A**

Local Exhaust **NO** Special
Mechanical (General) **NO** Other

Eye Protection **2.**

Other Protective Clothing or Equipment **3.**

Work/Hygienic Practices **4.**

1. USE GLOVES, IF NEEDED, TO AVOID PROLONGED OR REPEATED SKIN CONTACT.
2. WHEN CLEAN UP AND SWEEPING OPERATIONS ARE UNDERWAY GLASSES OR GOGGLES, IF NEEDED, TO PREVENT FLYING PARTICLES FROM ENTERING EYES.
3. COVERALLS OR OTHER PROTECTIVE CLOTHING, IF NEEDED, TO AVOID CONTAMINATING REGULAR CLOTHING, WHICH COULD RESULT IN PROLONGED OR REPEATED SKIN CONTACT.
4. KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME OR STRONG OXIDANTS. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. REMOVE CONTAMINATED CLOTHING. CLEANSE SKIN THOROUGHLY WITH SOAP AND WATER AFTER USE, BEFORE BREAKS AND MEALS, AND AT THE END OF WORK PERIOD.