

FEB 22 2001

14
Qua

MATERIAL SAFETY DATA SHEET

Ashland

Page 001
Date Prepared: 07/06/00
Date Printed: 01/25/01
MSDS No: 505.0257860-003.002

QUALITY TRACTOR HYDRAULIC FLUID

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: QUALITY TRACTOR HYDRAULIC FLUID
General or Generic ID: PETROLEUM BASED-LUBRICATING OIL

Company

Ashland
Ashland Distribution Co. &
Ashland Specialty Chemical Co.
P. O. Box 2219
Columbus, OH 43216
614-790-3333

Emergency Telephone Number:

1-800-ASHLAND (1-800-274-5263)
24 hours everyday

Regulatory Information Number:
1-800-325-3751

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
SOLVENT DEWAXED HEAVY PARA. PET. DISTIL.	64742-65-0	40.0- 50.0
ZINC COMPOUNDS		1.0- 7.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

May cause mild eye irritation.

Skin

May cause mild skin irritation. Prolonged or repeated contact may dry and crack the skin.

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

Symptoms of Exposure

stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), pain in the abdomen.

Target Organ Effects

No data

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland

Page 002
Date Prepared: 07/06/00
Date Printed: 01/25/01
MSDS No: 505.0257860-003.002

QUALITY TRACTOR HYDRAULIC FLUID

Developmental Information

No data

Cancer Information

Used motor oil has been shown to cause skin cancer in laboratory animals continually exposed by repeated applications. Avoid prolonged or repeated skin contact.

Other Health Effects

No data

Primary Route(s) of Entry

Skin contact.

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Swallowing

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Note to Physicians

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 3 - Swallowing) when deciding whether to induce vomiting.

5. FIRE FIGHTING MEASURES

Flash Point

395.0 F (201.6 C) COC

Explosive Limit

Not applicable

Continued on next page

FEB 22 2001

14

MATERIAL SAFETY DATA SHEET

Ashland

Page 003
Date Prepared: 07/06/00
Date Printed: 01/25/01
MSDS No: 505.0257860-003.002

QUALITY TRACTOR HYDRAULIC FLUID

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: aldehydes, carbon dioxide and carbon monoxide, hydrogen sulfide, ketones, nitrogen compounds, sulfur compounds, various hydrocarbons.

Fire and Explosion Hazards

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Dense smoke may be generated while burning.

Extinguishing Media

regular foam, water fog, carbon dioxide, dry chemical.

Fire Fighting Instructions

Water or foam may cause frothing which can be violent and possibly endanger the life of the firefighter. Water may be used to keep fire-exposed containers cool until fire is out. Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

NFPA Rating

Health - 1, Flammability - 1, Reactivity - 0

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

Large Spill

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on sand, clay, earth, floor absorbent, or other absorbent material and shoveled into containers.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Storage

Do not store near extreme heat, open flame, or sources of ignition.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Not required under normal conditions of use. However, if misting or splashing conditions exist, then safety glasses or chemical splash goggles are advised.

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland

Page 004
Date Prepared: 07/06/00
Date Printed: 01/25/01
MSDS No: 505.0257860-003.002

QUALITY TRACTOR HYDRAULIC FLUID

Skin Protection

Not normally required. However, wear resistant gloves such as nitrile rubber to prevent irritation which may result from prolonged or repeated skin contact with product., Wear normal work clothing covering arms and legs..

Respiratory Protections

Not required under normal conditions of use. However, if oil mists are generated above recommended PEL/TLV of 5 mg/m3, then a NIOSH/MSHA approved respirator is advised in absence of proper environmental control. (See your industrial hygienist.)

Engineering Controls

Not required under normal conditions of use. However, if unusual operating conditions exist, then provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below PEL/TLV (s).

Exposure Guidelines

Component

SOLVENT DEWAXED HEAVY PARA. PET. DISTIL. (64742-65-0)
OSHA VPEL 5.000 mg/m3 - TWA
ACGIH TLV 5.000 mg/m3 - TWA

ZINC COMPOUNDS
No exposure limits established

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point

Not applicable

Vapor Pressure

Not applicable

Specific Vapor Density

No data

Specific Gravity

.870 @ 60.00 F

Liquid Density

7.390 lbs/gal @ 60.00 F
.887 kg/l @ 15.60 C

Percent Volatiles (Including Water)

No data

Evaporation Rate

SLOWER THAN ETHYL ETHER

Appearance

No data

19

FEB 22 2001

MATERIAL SAFETY DATA SHEET

Ashland

Page 005
Date Prepared: 07/06/00
Date Printed: 01/25/01
MSDS No: 505.0257860-003.002

QUALITY TRACTOR HYDRAULIC FLUID

State

LIQUID

Physical Form

No data

Color

CLEAR TO LIGHT YELLOW

Odor

SLIGHT MINERAL

pH

Not applicable

Viscosity

61.5 cst @ 40 C

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: aldehydes, carbon dioxide and carbon monoxide, hydrogen sulfide, ketones, nitrogen compounds, sulfur compounds, various hydrocarbons.

Chemical Stability

Stable.

Incompatibility

Avoid contact with: strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

No data

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations.

MATERIAL SAFETY DATA SHEET

Ashland

Page 006
Date Prepared: 07/06/00
Date Printed: 01/25/01
MSDS No: 505.0257860-003.002

QUALITY TRACTOR HYDRAULIC FLUID

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

Not Regulated

Container/Mode:

CASES/SURFACE - NO EXCEPTIONS

NOS Component:

None

RQ (Reportable Quantity) - 49 CFR 172.101

Not applicable

15. REGULATORY INFORMATION

US Federal Regulations

TSCA (Toxic Substances Control Act) Status

TSCA (UNITED STATES) The intentional ingredients of this product are listed.

CERCLA RQ - 40 CFR 302.4

None

SARA 302 Components - 40 CFR 355 Appendix A

None

Section 311/312 Hazard Class - 40 CFR 370.2

Immediate(X) Delayed() Fire() Reactive() Sudden Release of
Pressure()

SARA 313 Components - 40 CFR 372.65

None

International Regulations

Inventory Status

Not determined

State and Local Regulations

California Proposition 65

None

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.