

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 21125 NAPA 765-1184 REARVIEW MIRROR ADHESIVE KIT PART 1
Item No: PTX194319Y
Product Type: Adhesive

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Percent	ACGIH 8 Hr. TWA:	OSHA 8 Hr. TWA:
POLYURETHANE METHACRYLATE RESIN MIXTURE	40-50		
HYDROXYALKYL METHACRYLATE 27813-02-1	10-20		
ETHOXYLATED BISPHENOL A DIMETHACRYLATE 41637-38-1	10-20		
ISOBORNYL METHACRYLATE 7534-94-3	10-20		
ACRYLIC ACID 79-10-7	1-10	2 ppm TWA; 5.9 mg/m3 TWA	10 ppm TWA; 30 mg/m3 TWA
GLYCIDOXYPROPYLTRIMETHOXY SILANE 2530-83-8	1-10		
BISPHENOL A FUMARATE RESIN 39382-25-7	1-10		
_DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	1-10		
1-ACETYL-2-PHENYLHYDRAZINE 114-83-0	0.1-1.0		
SACCHARIN 81-07-2	0.1-1.0	10mg/m3 nuisance dust	

3. HAZARDS IDENTIFICATION

Toxicity: May cause moderate skin irritation. Causes severe eye irritation.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation.
Signs and Symptoms of Exposure: Repeated skin contact may cause allergic skin reactions. May cause pain, redness or swelling of the eyes and excessive blinking and tear production.

Ingredients	Percent	NTP:	ACGIH Carcinogens	IARC:
ACRYLIC ACID 79-10-7	1-10		A4 - Not Classifiable as a Human Carcinogen	
SACCHARIN 81-07-2	0.1-1.0	Delisted April 2000		Group 3: Vol 73, Page 517: 1999

Medical Conditions Recognized as Being Aggravated by Exposure: Acrylic acid: Upper respiratory and lung diseases, dermatitis.

Product Name: 21125 NAPA 765-1184 REARVIEW MIRROR ADHESIVE KIT PART 1
Item No: PTX194319Y

4. FIRST AID MEASURES

Ingestion: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.
Inhalation: If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.
Skin Contact: Remove contaminated clothing. Wash area with soap and water. If irritation persists, seek medical attention.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): More than 200 degrees F. Method: Tag Closed Cup
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus.
Hazardous Products Formed by Fire or Thermal Decomposition: Irritating vapors.
Unusual Fire/Explosion Hazards: None
Lower Explosive Limit: 2.0% Acrylic acid
Upper Explosive Limit: 8.0% Acrylic acid

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage: Store below 100 degrees F.
Handling: Do not inhale vapors. Avoid prolonged skin contact. Keep away from eyes.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses or goggles.
Skin: Rubber or plastic gloves
Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits during the use of this product.
Respiratory Protection: An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Yellow liquid
Odor: SHARP
Boiling Point (°F): More than 300 degrees F.
pH: Does not apply
Solubility in Water: Insoluble
Specific Gravity: 1.1 @ 80 degrees F.
VOC Content(Wt.%): Not determined
Vapor Pressure: Not determined
Vapor Density (Air=1): Not Determined
Evaporation Rate: Not Determined

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions
Hazardous Polymerization: WILL NOT OCCUR
Incompatibilities: Avoid contact with bases and strong oxidizers.
Conditions to Avoid: High temperatures.
Hazardous Products Formed by Fire or Thermal Decomposition: Irritating vapors.

11. TOXICOLOGICAL INFORMATION

See Section 3

Product Name: 21125 NAPA 765-1184 REARVIEW MIRROR ADHESIVE KIT PART 1
Item No: PTX194319Y

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.
US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name: Unrestricted
Hazard Class: NONE
UN/ID Number: None
Marine Pollutant: None

IATA

Proper Shipping Name: Unrestricted
Class or Division: None
UN/NA Number: None

IMDG

Proper Shipping: Unrestricted
Hazard Class: None
UN Number: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.
ACRYLIC ACID, DIMETHYLBENZYL HYDROPEROXIDE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present.

TSCA Inventory Status:

All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 1, REACTIVITY 1
Estimated HMIS Classification: HEALTH 2, FLAMMABILILTY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.
HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd Health and Safety Manager
Company: Permatex. Inc. 10 Columbus Blvd. Hartford, CT 06106
Telephone Number: 1-87-Permatex (877) 376-2839
Revision Date: 09/12/2002

Revision Number: 0