

Permatex, Inc.  
 10 Columbus Blvd.  
 Hartford, CT 06106 USA  
 Telephone: 1-87-Permatex  
 (877) 376-2839  
 Emergency: 800-255-3924

## Material Safety Data Sheet

### 1. PRODUCT IDENTIFICATION

**Product Name:** 765-2694 NAPA THE RIGHT STUFF 4 OZ AE  
**Item No:** 25225  
**Product Type:** Elastomeric rubber (pressurized)

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Percent	ACGIH 8 Hr. TWA:	OSHA 8 Hr. TWA:
CALCIUM CARBONATE 471-34-1	25-50	10 mg/m <sup>3</sup> total dust	15 mg/m <sup>3</sup> dust; 5 mg/m <sup>3</sup> respir
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	20-40	Not Listed	Not Listed
POLYDIMETHYLSILOXANE 63148-62-9	5-20	Not Listed	Not Listed
VINYL OXIMINOSILANE 2224-33-1	1-10	Not Listed	Not Listed
STEARIC ACID 57-11-4	1-10	Not Listed	Not Listed
MODIFIED SILICON DIOXIDE 68611-44-9	0.5-5.0	Not Listed	Not Listed
CARBON BLACK 1333-86-4	0.5-5.0	3.5 mg/m <sup>3</sup>	3.5 mg/m <sup>3</sup> TWA
Nitrogen 7727-37-9	0.5-2.0	Not Listed	Not Listed
2-BUTANONE OXIME 96-29-7	****	Not Listed	Not Listed

### 3. HAZARDS IDENTIFICATION

**Toxicity:** Note: This product does not contain microcrystalline silica. May cause eye and skin irritation. May irritate lips, gums, tongue, mouth, nose and throat. May be harmful if swallowed. When heated to temperatures above 300 degrees F. in the presence of air, this product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Safe handling conditions may be maintained by keeping vapor concentrations below the OSHA permissible limit for formaldehyde. \*\*\*\*When this product is exposed to moisture, up to 10% methyl ethyl ketoxime may be formed.

**Primary Routes of Entry:** Eye and skin contact, ingestion, inhalation.

**Signs and Symptoms of Exposure:** Methyl ethyl ketoxime produced during cure is toxic and irritates eyes, nose and throat. Overexposure may cause eye and skin redness. Overexposure to nitrogen propellant (only released if can is punctured) may cause headache, drowsiness, dizziness, excitation, excess salivation, vomiting, unconsciousness.

Ingredients	Percent	NTP:	ACGIH Carcinogens	IARC:
CARBON BLACK 1333-86-4	0.5-5.0		Group A4	Group 2B; Vol. 65, pg 149, 1996

**Medical Conditions Recognized as Being Aggravated by Exposure:** None known

### 4. FIRST AID MEASURES

**Ingestion:** If swallowed, seek medical advice immediately and show this container or label  
**Inhalation:** Move to fresh air in case of accidental inhalation of vapors. Oxygen or artificial respiration if needed.  
**Skin Contact:** Wipe off paste with paper towel or cloth. If skin irritation persists, call a physician  
**Eye Contact:** In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice

### 5. FIRE FIGHTING MEASURES

**Flash Point (°F/C):** More than 200 degrees F. (base material) Method: Tag Closed Cup

**Recommended Extinguishing Media:  
Special Fire-Fighting Procedures:**

Carbon Dioxide, Dry Chemicals, Foam.  
\*\*\*Warning: This container is pressurized with nitrogen. Do not remove rubber plug. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers.  
Formaldehyde, Silica fume, Oxides of carbon.

**Hazardous Products Formed by Fire or Thermal  
Decomposition:  
Unusual Fire/Explosion Hazards:**

Contents under pressure. Heated cans may burst. Use equipment or shielding to protect personnel from bursting containers.

**Lower Explosive Limit:  
Upper Explosive Limit:**

Not determined  
Not determined

**6. ACCIDENTAL RELEASE MEASURES**

**Spill Procedures:** Wipe or scrape up spill material. Maintain good ventilation for large spills. Place scrap material in a well-ventilated area and allow to cure to rubber. Clean up spills thoroughly as residue is slippery.

**7. HANDLING AND STORAGE**

**Storage:** Store in a dry area below 90 degrees F. Keep container closed when not in use. Exposure to high temperatures may cause container to burst.

**Handling:** Avoid contact with skin and eyes. Do not inhale vapors.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Eyes:** Safety glasses.  
**Skin:** rubber or plastic gloves  
**Ventilation:** Provide adequate ventilation  
**Respiratory Protection:** not required under normal use In case of insufficient ventilation, wear suitable respiratory equipment

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance:** Black paste  
**Odor:** MILD  
**Boiling Point (°F):** Not applicable, polymeric material  
**pH:** 7-8  
**Solubility in Water:** Polymerized  
**Specific Gravity:** 1.34  
**VOC Content(Wt.%):** 4.0% by weight; 52.5 g/l for base material  
**Vapor Pressure:** Less than 5 mm Hg  
**Vapor Density (Air=1):** 3.0  
**Evaporation Rate:** Slower than butyl acetate

**10. STABILITY AND REACTIVITY**

**Chemical Stability:** Stable at normal conditions  
**Hazardous Polymerization:** WILL NOT OCCUR  
**Incompatibilities:** Strong oxidizers. Polymerized by contact with moisture.  
**Conditions to Avoid:** Exposure to moisture Heat  
**Hazardous Products Formed by Fire or Thermal  
Decomposition:** Formaldehyde, Silica fume, Oxides of carbon.

**11. TOXICOLOGICAL INFORMATION**

See Section 3

**12. ECOLOGICAL INFORMATION**

No data available

**13. DISPOSAL CONSIDERATIONS**

**Recommended Method of Disposal:** Disposal should be made in accordance with federal, state and local regulations.  
**US EPA Waste Number:** D003 - (Can under pressure) Hazardous waste per 40CFR 261.23(6)

**14. TRANSPORTATION INFORMATION**

DOT (49CFR 172)

**Domestic Ground Transport**

**DOT Shipping Name:** CONSUMER COMMODITY  
**Hazard Class:** ORM-D  
**UN/ID Number:** None  
**Marine Pollutant:** None

**IATA**

**Proper Shipping Name:** Consumer Commodity  
**Class or Division:** Class 9  
**UN/NA Number:** ID 8000

**IMDG**

**Proper Shipping:** Aerosols, Limited Quantity  
**Hazard Class:** Class 2.2  
**UN Number:** UN 1950

**15. REGULATORY INFORMATION**

**SARA 313 Chemicals:** The following component(s) is listed as a SARA Section 313 Toxic Chemical.

**SARA 313 Information**

NONE

**CALIFORNIA PROP 65:**

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

**TSCA Inventory Status:**

**Listed on Inventory:** YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

**16. OTHER INFORMATION**

**Estimated NFPA Rating:** HEALTH 1, FLAMMABILITY 1, REACTIVITY 0

**Estimated HMIS Classification:** HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

**Prepared By:** Denise Boyd, Health and Safety Manager  
**Company:** Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA  
06106

**Revision Date:** 02/23/2004

**Revision Number:** 2

**Telephone Number:** 1-87-Permatex (877) 376-2839