

mac2500

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 001

Date Prepared: 10/14/03

Date Printed: 07/03/06

MSDS No: 503.0172287-006.001

MAC'S TAR AND BUG REMOVER 2500

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: MAC'S TAR AND BUG REMOVER 2500

SAP Material No: NM2500

General or Generic ID: AUTOMOTIVE CHEMICAL

Company

The Valvoline Company

P.O. Box 14000

Lexington, KY 40512

Telephone Numbers

Emergency: 1-800-274-5263

Information: 1-859-357-7206

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
KEROSENE	8008-20-6	81.0- 91.0
AROMATIC PETROLEUM DISTILLATES	64742-94-5	6.0- 16.0
SURFACTANT	Trade Secret	0.0- 8.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Can cause eye irritation.

Skin

May cause mild skin irritation. Prolonged or repeated contact may dry and crack the skin.

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

mac2500

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 002

Date Prepared: 10/14/03

Date Printed: 07/03/06

MSDS No: 503.0172287-006.001

MAC'S TAR AND BUG REMOVER 2500

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful.

Symptoms of Exposure

stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), and death.

Target Organ Effects

No data

Developmental Information

No data

Cancer Information

This product (or a component) is a petroleum-derived material. Similar materials and certain compounds occurring naturally in petroleum oils have been shown to cause skin cancer in laboratory animals following repeated exposure without washing or removal.

Other Health Effects

No data

Primary Route(s) of Entry

Inhalation, Skin contact.

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

mac2500

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 003

Date Prepared: 10/14/03

Date Printed: 07/03/06

MSDS No: 503.0172287-006.001

MAC'S TAR AND BUG REMOVER 2500

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Swallowing

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Note to Physicians

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 3 - Swallowing) when deciding whether to induce vomiting. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin.

5. FIRE FIGHTING MEASURES

Flash Point

140.0 - 160.0 F (60.0 - 71.1 C) TCC

Explosive Limit

(for component) Lower .7 %

mac2500

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 004

Date Prepared: 10/14/03

Date Printed: 07/03/06

MSDS No: 503.0172287-006.001

MAC'S TAR AND BUG REMOVER 2500

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Fire and Explosion Hazards

Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Extinguishing Media

regular foam, carbon dioxide, dry chemical.

Fire Fighting Instructions

Water or foam may cause frothing which can be violent and possibly endanger the life of the firefighter. Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

NFPA Rating

Health - 1, Flammability - 2, Reactivity - 0

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

mac2500

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 005

Date Prepared: 10/14/03

Date Printed: 07/03/06

MSDS No: 503.0172287-006.001

MAC'S TAR AND BUG REMOVER 2500

Large Spill

Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal. Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Storage

Not applicable

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

mac2500

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 006

Date Prepared: 10/14/03

Date Printed: 07/03/06

MSDS No: 503.0172287-006.001

MAC'S TAR AND BUG REMOVER 2500

Skin Protection

Wear resistant gloves such as: neoprene, nitrile rubber, To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Exposure Guidelines

Component

KEROSENE (8008-20-6)

ACGIH TLV 200.000 mg/m³ - TWA ((Skin))

AROMATIC PETROLEUM DISTILLATES (64742-94-5)

No exposure limits established

SURFACTANT

No exposure limits established

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point

(for component) > 300.0 F (148.8 C) @ 760.00 mmHg

mac2500

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 007

Date Prepared: 10/14/03

Date Printed: 07/03/06

MSDS No: 503.0172287-006.001

MAC'S TAR AND BUG REMOVER 2500

Vapor Pressure

(for component) 5.000 mmHg @ 77.00 F

Specific Vapor Density

> 1.000 @ AIR=1

Specific Gravity

.840 @ 77.00 F

Liquid Density

6.990 lbs/gal @ 77.00 F

.840 kg/l @ 25.00 C

Percent Volatiles (Including Water)

No data

Evaporation Rate

SLOWER THAN ETHYL ETHER

Appearance

No data

State

LIQUID

Physical Form

N/A

Color

CLEAR AMBER

Odor

No data

pH

Not applicable

mac2500

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 008

Date Prepared: 10/14/03

Date Printed: 07/03/06

MSDS No: 503.0172287-006.001

MAC'S TAR AND BUG REMOVER 2500

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Chemical Stability

Stable.

Incompatibility

Avoid contact with: strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

No data

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Destroy by liquid incineration. Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

FLAMMABLE LIQUIDS, N.O.S.,3,UN 1993,III

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 009

Date Prepared: 10/14/03

Date Printed: 07/03/06

MSDS No: 503.0172287-006.001

MAC'S TAR AND BUG REMOVER 2500

Container/Mode:

CASES/SURFACE - NO EXCEPTIONS

NOS Component:

KEROSENE

RQ (Reportable Quantity) - 49 CFR 172.101

Product Quantity (lbs) Component

9328

NAPHTHALENE

15. REGULATORY INFORMATION

US Federal Regulations

TSCA (Toxic Substances Control Act) Status

TSCA (UNITED STATES) The intentional ingredients of this product are listed.

CERCLA RQ - 40 CFR 302.4

None

SARA 302 Components - 40 CFR 355 Appendix A

None

Section 311/312 Hazard Class - 40 CFR 370.2

Immediate(X) Delayed(X) Fire(X) Reactive() Sudden Release of Pressure()

SARA 313 Components - 40 CFR 372.65

None

International Regulations

Inventory Status

Not determined

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 010

Date Prepared: 10/14/03

Date Printed: 07/03/06

MSDS No: 503.0172287-006.001

MAC'S TAR AND BUG REMOVER 2500

State and Local Regulations

California Proposition 65

None

New Jersey RTK Label Information

KEROSENE

8008-20-6

Pennsylvania RTK Label Information

KEROSINE (PETROLEUM)

8008-20-6

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

