

27013-1102

MATERIAL SAFETY DATA SHEET

Product: 803 Satin Sealer

SECTION I -- SUPPLIER INFORMATION

Manufacturer : Old World Art
 Address : 1953 South Lake Place
 City, St, Zip : Ontario, CA 91761
 Phone : (909)947-4928 (909)947-9945 Fax(909)923-1185
 Date : 01/01/2003

SECTION II -- HAZARDOUS INGREDIENT INFORMATION

| Ingredient | % Wt. | PeI-OSHA | TLV-ACGIH |
|-------------------|-------|----------|-----------|
| MINERAL SPIRITS | 21.6 | 100 ppm | 100 ppm |
| PETROLEUM NAPHTHA | 52.1 | 300 ppm | 300 ppm |

SECTION III -- PHYSICAL/CHEMICAL CHARACTERISTICS

Appearance and Odor : SOLVENT THINNED CLEAR LIQUID
 Boiling Point : 135 F
 Specific Gravity (Water=1) :
 Melting Point : N/A
 Vapor Pressure : 1 mm Hg @ 68 F
 Vapor Density (Air=1) : HEAVIER THAN AIR
 Evaporation Rate (Butyl Acetate=1) : SLOWER THAN ETHER

SECTION IV -- FIRE AND EXPLOSION HAZARD DATA

Flash Point : Over 100 F P.M.C.C. DRY LEL 1.0% COMBUSTIBLE
 Flammable Limits : NA
 Extinguishing Media : FOAM, DRY CHEM., CO2, H2O SPRAY
 Special Fire Fighting Procedures: DO NOT USE WATER STREAM ON BURNING LIQUID COOL EXPOSED CONTAINERS WITH WATER.
 Unusual Fire & Explosion Hazards: EXTREMELY FLAMMABLE. KEEP CONTAINERS CLOSED WHEN NOT IN USE. ISOLATE FROM FLAME AND SPARKS. AVOID TOBACCO SMOKING WHEN USING THIS MATERIAL.

SECTION V -- REACTIVITY DATA

Stability : STABLE
 Conditions to Avoid : NONE
 Incompatibility : NA
 Hazardous Polymerization: BURNING WILL PRODUCE TOXIC FUMES

SECTION VI -- HEALTH HAZARD DATA

Medical Conditions Generally Aggravated by Exposure : A review of available data does not identify any worsening of existing conditions not elsewhere mentioned in this MSDS.
 Effects of Over Exposure : METHANOL VAPORS CAUSE LOCAL IRRITATION OF EYES, HEADACHE, SENSATION OF HEAT, FATIGUE AND DROWSINESS.

Emergency First Aid Procedures :

Inhalation: REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION OR OXYGEN IF NEEDED.

Ingestion: INDUCE VOMITING IF VICTIM IS CONSCIOUS. CALL A PHYSICIAN.

Skin Contact: WASH SKIN WITH SOAP AND WATER.

Eye Contact: FLUSH EYES WITH PLENTY OF WATER FOR 15 MINUTES. CALL A PHYSICIAN IF IRRITATION PERSISTS.

SECTION VII -- PRECAUTIONS FOR SAFE HANDLING AND USE

Spill and Leak Procedure: REMOVE SOURCES OF IGNITION. FLUSH WITH PLENTY OF WATER AND COVER WITH INERT ABSORBENT MATERIAL AND REMOVE TO SUITABLE DISPOSAL CONTAINER.

Waste Disposal: OBEY RELEVANT LOCAL, STATE AND FEDERAL LAWS.

Precautions to be taken in handling and storage: PROTECT FROM EXTREME COLD.

SECTION VIII -- CONTROL MEASURES

Respiratory Protection: A NIOSH/MSHA APPROVED RESPIRATOR AS NECESSARY.

Ventilation: GENERAL; LOCAL EXHAUST VENTILATION AS NECESSARY TO CONTROL MIST OR DUST.

Protective Gloves: IMPERMEABLE GLOVES TO MINIMIZE SKIN CONTACT.

Eye Protection: CHEMICAL GOGGLES OR FACE SHIELD.

Other Protective Measures:

*THIS INFORMATION IS FURNISHED WITHOUT WARRANTY, REPRESENTATION, INDUCEMENT OR LICENSE OF ANY KIND, EXCEPT THAT IT IS BELIEVED TO BE ACCURATE, AND OUR COMPANY DOES NOT ASSUME ANY LEGAL RESPONSIBILITY FOR THE USE OR RELIANCE UPON SAME. CUSTOMERS ARE ENCOURAGED TO CONDUCT THEIR OWN TESTS. BEFORE USING ANY PRODUCT READ ITS LABEL.