

**VANDALISM REMOVER #XA006**

Quick Identifier (In Plant Common Name)

# Material Safety Data Sheet

Manufactured For: **PRO-LINK, INC.**  
 Name & Address: CANTON, MA 02021


Emergency Telephone No.: 1-800.74.LINKS Mon. - Fri. 8-5  
 (800) 255-3924 24 HOURS

**HMIS Symbol:**

Health	2
Flammability	4
Reactivity	0

**HMIS----** **NFPA**  
 Minimal - 0 - Insignificant  
 Slight - 1 - Slight  
 Moderate - 2 - Moderate  
 Serious - 3 - High  
 Severe - 4 - Extreme

**NFPA Symbol:**



Date Prepared: June 3, 2002 Prepared By: Date:

**SECTION 1 - IDENTITY**

Common Name: (used on label) Vandalism Remover #XA006  
 (Trade name & Synonyms)

Chemical Name: Mixture packaged in pressurized aerosol spray can.

**SECTION 2 - HAZARDOUS INGREDIENTS**

Principal Hazardous Component(s)	CAS No.	OSHA PEL	ACGIH TLV	Other Limits
Propane	74-98-6	Not Est.	1000 ppm	
Butane	106-97-8	Not Est.	800 ppm	
*Toluene (1)	108-88-3	200 ppm	100 ppm	
Diacetone Alcohol	123-42-2	50 ppm	50 ppm	
*2-Butanone	78-93-3	200 ppm	200 ppm	300 ppm (STEL)

\*Section 313 Supplier Notification - Indicates hazardous ingredients which are toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

**SECTION 3 - PHYSICAL & CHEMICAL CHARACTERISTICS**

Boiling Point	232°F (111.1°C)	Specific Gravity (H <sub>2</sub> O=1)	0.84 - 0.88 g/ml	Vapor (Propellant) Pressure (PSI)	68 - 72 psig
Volatile Organic Content (% Weight)	98%	Evaporation Rate (BuAc=1)	2.0	pH	N/A
Solubility In Water	20%	Appearance and Odor	Clear Liquid, Solvent Odor		

**SECTION 4 - FIRE & EXPLOSION DATA**

Flammability (per flame projection)	Extremely Flammable	Flammable Limits in Air % by Volume	Lower 1.9%	Upper 9.5%	Extinguisher Media	Foam, Dry Chemical, CO <sub>2</sub>
-------------------------------------	---------------------	-------------------------------------	------------	------------	--------------------	-------------------------------------

Special Fire Fighting Procedures: Keep containers cool using water spray. Use proper equipment to protect personnel from bursting containers.

Unusual Fire and Explosion Hazards: Contents under pressure. Do not expose to temperatures exceeding 120°F. as containers may vent, rupture or burst.

**SECTION 5 - PHYSICAL HAZARDS**

Stability: Unstable  Conditions Open Flames; Hazardous May Occur  Conditions  
 Stable  to Avoid Temp. > 120°F. Polymerization Will not Occur  to Avoid None

Incompatibility (Materials to Avoid): Strong oxidizers, strong alkalis, strong mineral acids.

Hazardous Decomposition Products: CO, CO<sub>2</sub>, various hydrocarbons.

**SECTION 6 - HEALTH HAZARDS**

Routes of Entry      Inhalation: Yes      Eyes / Skin: Yes      Ingestion: Unlikely

Signs and Symptoms of Exposure (Acute & Chronic)      May cause skin and eye irritation. Ingestion or inhalation at high concentrations may cause nausea, dizziness and headaches.

Medical Conditions Generally Aggravated by Exposure      May aggravate lung, liver and kidney disorders.

Chemical Listed as Carcinogen or Potential Carcinogen      National Toxicology Program      Yes  No       I.A.R.C. Monographs      Yes  No       OSHA      Yes  No

**Emergency and First Aid Procedures**

- 1. Inhalation      Remove victim to fresh air. Apply artificial respiration if necessary.  
Get medical attention.
- 2. Eyes      Flush eyes with water for at least 15 minutes. Get medical attention if irritation persists.
- 3. Skin      Wash affected areas w/ soap & water. Get medical attention if irritation persists.
- 4. Ingestion      Do not induce vomiting. Get medical attention immediately.

**SECTION 7 - SPECIAL PROTECTION INFORMATION**

Respiratory Protection (Specify Type)      None required for normal use.

Ventilation      Local Exhaust      Maintain adequate ventilation      Mechanical (General)      N/A      Special      N/A      Other      N/A

Protective Gloves      Wear gloves if contact causes skin irritation.      Eye Protection      Wear safety glasses or goggles.

Other Protective Clothing or Equipment      None required.

**SECTION 8 - SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES**

Precautions to be Taken Handling and Storage      Do not store at temperatures above 120°F. Do not puncture or incinerate containers. Keep out of reach of children.

Other Precautions      Read label precautions carefully.

Steps to be Taken in Case Material is Released or Spilled      Soak up spilled liquid with absorbent material. Place in closed drum for proper disposal.

Waste Disposal Methods      Dispose of in accordance with local, state, and federal regulations.

California Prop. 65 Warning:      This product contains a chemical(s) known to the State of California to cause cancer and reproductive harm.

We believe all information given is accurate. It is offered in good faith, but without guarantee. Since conditions are beyond our control, user assumes all responsibility and risk.