

MSDS - Material Safety Data Sheet

Product Name: TITE SEAL PLASTIC PIPE CLEANER

MSDS No.: T6516

I. Basic Information:

Manufacturer: RADIATOR SPECIALTY COMPANY
Address: 600 RADIATOR ROAD
City, ST Zip: INDIAN TRAIL, NC 28079
Emergency Contact: Rocky Mountain Poison Control Center
Emergency Telephone Number: 303-623-5716
Contact: Robert Geer
Information Telephone Number: 704-688-3430



2	Health
3	Flammability
0	Reactivity
H	Pers. Protection

Last Update: 12/05/2005

Chemical State: Liquid Gas Solid
Chemical Type: Pure Mixture

II. Ingredients:

Trade Secret

CAS No.	Chemical Name	% Range	EHS		IARC		SARA		OSHA PEL	ACGIH TLV	Other Limits
			NTP		SUB	Z	313				
67641	Acetone	60.0 - 85.0							750 ppm	750 ppm	
108941	Cyclohexanone	1.0 - 11							25 ppm	25 ppm	
78933	Methyl ethyl ketone	11.0 - 33						X	200 ppm	200 ppm	

III. Hazardous Identification:

Hazard Category:

Acute Chronic Fire Pressure Reactive

Hazardous Identification Information:

Danger: Extremely Flammable. Vapors may cause Flash Fire. Harmful or Fatal if Swallowed. Vapor Harmful. Eye and Skin Irritant. Keep Away From Children and Animals..

IV. First Aid Measures:

Route(s) of Entry:

Inhalation, Skin Contact, Eyes and Ingestion.

Health Hazards (Acute and Chronic):

Affects central nervous system. Causes irritation to skin.

Signs and Symptoms:

Eye Contact: overexposure may result in severe eye injury with corneal or conjunctival inflammation on contact with the liquid. Vapors slightly uncomfortable.
 Skin Absorption: Prolonged or widespread exposure may result in irritation and dermatitis.
 Inhalation: Severe overexposure may result in nausea, dizziness, headache. Can cause drowsiness, irritation of eyes and nasal passages.
 Ingestion: Moderately toxic. May cause nausea, vomiting, diarrhea. May cause mental sluggishness.

Medical Conditions Generally Aggravated by Exposure:

Individuals with pre-existing diseases of the eyes, skin, or respiratory system may have increased susceptibility to the toxicity of excessive exposures.

Emergency and First Aid Procedures:

MSDS - Material Safety Data Sheet

Product Name: TITE SEAL PLASTIC PIPE CLEANER

MSDS No.: T6516

Eye Contact: Flush eyes with clean water for 15 minutes while lifting eyelids and get prompt medical attention.

Skin Contact: Wash with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Launder contaminated clothing before reuse.

Inhalation: Remove to fresh air. If breathing becomes difficult get prompt medical attention.

Ingestion: DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately.

Other Health Warnings:

Vomiting and subsequent aspiration into the lungs may lead to chemical pneumonia and pulmonary edema which is a potentially fatal condition.

V. Fire Fighting Measures:

Flash Point: - 6°F

Lower Explosive Limit: 2.1

Upper Explosive Limit: 13.0

F.P. Method: TCC

Fire Extinguishing Media: Ansul "Purple K" potassium bicarbonate dry chemical, carbon dioxide, National Aer-O-Foam universal alcohol resistant foam, water spray.

Special Fire Fighting Procedures:

Wear self-contained positive pressure breathing apparatus and protective clothes. Cool containers with a water fog. Do not use forced water stream as this could cause the fire to spread. Use shield to protect from rupturing and venting containers.

Unusual Fire and Explosion:

Fire hazard because of low flash point and high volatility. Vapors are heavier than air and may travel to source of ignition.

VI. Accidental Release Measures:

Steps to be Taken in Case Material is Released or Spilled:

Eliminate all ignition sources. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc). Using a non-metallic scoop, place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid using an explosion proof vacuum to recover material. Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occurred.

VII. Handling and Storage:

Precautions to be Taken:

Store in the shade between 40°F - 110°F. Keep away from heat, sparks, open flame and other sources of ignition. Avoid prolonged breathing of vapor. Use with adequate ventilation. Avoid contact with eyes, skin, and clothing. Train employees on all special handling procedures before they work with this product.

Other Precautions:

Follow all precautionary information given on container label, product bulletins and our solvent cementing literature. All handling equipment should be electrically grounded.

VIII. Exposure Controls/Personal Protection:

Ventilation Requirements:

See Section 2 for applicable exposure limits. Maintain adequate ventilation. Avoid breathing vapors. In restricted areas, use approved chemical filter designed to remove vapor. In confined areas, use approved air line type respirator or hood. A self-contained breathing apparatus is required for vapor concentrations above TLV limits.

Personal Protective Equipment:

See Section 2 for applicable exposure limits. For prolonged exposure wear protective safety glasses, PVA coated gloves, and apron. A source of running water should be available to flush or wash the eyes and skin in case of contact.

MSDS - Material Safety Data Sheet

Product Name: TITE SEAL PLASTIC PIPE CLEANER

MSDS No.: T6516

IX. Physical and Chemical Properties:

Boiling Point: 133°F

Melting Point: N/A

Evaporation Rate (Butyl Acetate = 1): 6-11

Vapor Pressure (mm Hg.): 190

Specific Gravity (H2O = 1): 0.79800

Vapor Density (AIR = 1): 2.0

Solubility In Water: Completely soluble in water

Appearance and Odor: Colorless liquid with ether-like odor

Other Information: Percent Volatile by Volume: 100%

VOC Content: 800 grams/liter

Maximum VOC emission does not exceed 250 grams/liter when applied and tested per SCAQMD Rule 1168, Test Method 316A.

X. Stability and Reactivity:

Stability:

Stable

Incompatibility (Materials to Avoid):

Caustics, ammonia, inorganic acids, chlorinated compounds, strong oxidizers and isocyanates.

Decomposition/By Products:

Carbon monoxide, carbon dioxide, hydrogen chloride and smoke

Hazardous Polymerization:

Will not occur

XI. Toxicological Information:

N/D

XII. Ecological Information:

N/D

XIII. Disposal Considerations:

DISPOSAL: This container may be recycled in a recycling centers when empty. Before offering for recycling, empty the can or bottle by using the product according to the label. If recycling is not available, wrap the container and discard in the trash. Dispose of unused product in accordance with all local, state government and federal laws and regulations

XIV. Transport Information:

Shipping information for containers less than one liter:

DOT Shipping Name: Consumer Commodity

DOT Hazard Class: ORM-D

Shipping information for liter containers and above:

DOT Shipping Name: Flammable Liquid N.O.S.

(Acetone, Methyl Ethyl Ketone)

DOT Hazard Class: 3

Identification Number: UN1993

Packaging Group: II

Label Required: Flammable Liquid

XV. Regulatory Information:

See Section 2 for SARA Reportable Chemicals.

USA TSCA: All components of this material are listed on the US TSCA Inventory.

MSDS - Material Safety Data Sheet

Product Name: TITE SEAL PLASTIC PIPE CLEANER

MSDS No.: T6516

XVI. Other Information:

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye.
KEEP AWAY FROM CHILDREN AND ANIMALS!

N/E: Not Established
N/D: Not Determined
N/A: Not Applicable
N/AV: Not Available

While Radiator Specialty Company believes this data is accurate as of the revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered solely for information, investigation, and verification. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.