

Material Safety Data Sheet

24 Hour Assistance:
1-847-367-7700
Rust-Oleum Corp.
www.rustoleum.com

Section 1 - Chemical Product / Company Information

Product Name: Rust-Oleum Stops Rust Enamel Aerosol
Top Coats
Revision Date: 05/06/2003
7721830, 7722830, 7723830, 7724830,
7727830, 7729830, 7731830, 7733830,
7738830, 7740830, 7747830, 7754830,
7755830, 7762830, 7763830, 7765830,
Identification Number: 7768830, 7770830, 7771830, 7775830,
7776830, 7779830, 7783830, 7784830,
7786830, 7789830, 7790830, 7792830,
7794830, 7796830, 7797830, 7798830

Product Use/Class: Topcoats/Aerosol
Supplier: Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, IL 60061
USA
Manufacturer: Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, IL 60061
USA
Preparer: Department, Regulatory

Section 2 - Composition / Information On Ingredients

| Chemical Name | CAS Number | Weight % Less Than | ACGIH TLV-TWA | ACGIH TLV-STEL | OSHA PEL-TWA | OSHA PEL-CEILING |
|---------------------------|------------|--------------------|---------------|----------------|--------------|------------------|
| Liquidified Petroleum Gas | 68476-85-7 | 35.0 | 1000 PPM | N.E. | 1000 PPM | N.E. |
| Acetone | 67-64-1 | 30.0 | 500 PPM | 750 PPM | 750 PPM | N.E. |
| Toluene | 108-88-3 | 25.0 | 50 PPM | N.E. | 200 PPM | 300 PPM |
| Xylene | 1330-20-7 | 20.0 | 100 PPM | 150 PPM | 100 PPM | N.E. |
| Titanium Dioxide | 13463-67-7 | 15.0 | 10 mg/m3 | N.E. | 10 mg/m3 | N.E. |
| Magnesium Silicate | 14807-98-6 | 15.0 | 10mg/m3 | N.E. | 15mg/m3 | N.E. |
| Stoddard Solvents | 8052-41-3 | 10.0 | 100 PPM | N.E. | 500 PPM | N.E. |
| Aliphatic Hydrocarbon | MIXTURE | 10.0 | 300 PPM | N.E. | 300 PPM | N.E. |
| Propylene Carbonate | 108-32-7 | 10.0 | N.E. | N.E. | N.E. | N.E. |
| Ethylbenzene | 100-41-4 | 10.0 | 100 PPM | 125 PPM | 100 PPM | N.E. |
| Barium Sulfate | 7727-43-7 | 5.0 | 10MG/M3 | N.E. | 15MG/M3 | N.E. |
| Aromatic Hydrocarbon | 64742-95-6 | 5.0 | N.E. | N.E. | N.E. | N.E. |
| Super High Flash Naphtha | 64742-95-6 | 5.0 | N.E. | N.E. | N.E. | N.E. |
| Pigment Red 170 | 2786-76-7 | 5.0 | N.E. | N.E. | N.E. | N.E. |
| 1,2,4-Trimethylbenzene | 95-63-6 | 5.0 | 25 PPM | N.E. | N.E. | N.E. |
| Pigment Black 7 | 1333-86-4 | 5.0 | 3.5 mg/m3 | N.E. | 3.5 mg/m3 | N.E. |
| Red Iron Oxide | 1332-37-2 | 5.0 | 10 mg/M3 | N.E. | 15 mg/m3 | N.E. |
| Pigment Green 7 | 1328-53-6 | 1.0 | N.E. | N.E. | N.E. | N.E. |
| Calcium Carbonate | 1317-65-3 | 0.1 | 10 mg/m3 | N.E. | 15 mg/m3 | N.E. |

Section 3 - Hazards Identification

*** Emergency Overview ***: Contents Under Pressure. Harmful if inhaled. May affect the brain or nervous system causing dizziness, headache or nausea. Vapors may cause flash fire or explosion. Extremely flammable liquid and vapor. Harmful if swallowed.

Effects Of Overexposure - Eye Contact: Causes eye irritation.

Effects Of Overexposure - Skin Contact: Prolonged or repeated contact may cause skin irritation. Substance may cause slight skin irritation.

Effects Of Overexposure - Inhalation: High vapor concentrations are irritating to the eyes, nose, throat and lungs. Avoid breathing vapors or mists. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Harmful if inhaled.

Effects Of Overexposure - Ingestion: Aspiration hazard if swallowed; can enter lungs and cause damage. Substance may be harmful if swallowed.

Effects Of Overexposure - Chronic Hazards: IARC lists Ethylbenzene as a possible human carcinogen (group 2B). May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Overexposure to xylene in laboratory animals has been associated with liver abnormalities, kidney, lung, spleen, eye and blood damage as well as reproductive disorders. Effects in humans, due to chronic overexposure, have included liver, cardiac abnormalities and nervous system damage. Overexposure to toluene in laboratory animals has been associated with liver abnormalities, kidney, lung and spleen damage. Effects in humans have included liver and cardiac abnormalities.

Contains carbon black. Chronic inflammation, lung fibrosis, and lung tumors have been observed in some rats experimentally exposed for long periods of time to excessive concentrations of carbon black and several insoluble fine dust particles. Tumors have not been observed in other animal species (i.e., mouse and hamster) under similar circumstances and study conditions. Epidemiological studies of North American workers show no evidence of clinically significant adverse health effects due to occupational exposure to carbon black. Carbon black is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC and is proposed to be listed as A4- "not classified as a human carcinogen" by the American Conference of Governmental Industrial Hygienists. Significant exposure is not anticipated during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of carbon black in the formula.

Primary Route(s) Of Entry: Skin Contact, Skin Absorption, Inhalation, Eye Contact

Section 4 - First Aid Measures

First Aid - Eye Contact: Hold eyelids apart and flush with plenty of water for at least 15 minutes. Get medical attention.

First Aid - Skin Contact: Wash with soap and water. Get medical attention if irritation develops or persists.

First Aid - Inhalation: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

First Aid - Ingestion: Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention.

Section 5 - Fire Fighting Measures

Flash Point: -156 F
(Setaflash)

LOWER EXPLOSIVE LIMIT: 1.0 %
UPPER EXPLOSIVE LIMIT : 9.5 %

Extinguishing Media: Dry Chemical, Foam, Water Fog

Unusual Fire And Explosion Hazards: Keep containers tightly closed. Vapors can travel to a source of ignition and flash back. Vapors may form explosive mixtures with air. FLASH POINT IS LESS THAN 20 DEG. F. - EXTREMELY FLAMMABLE LIQUID AND VAPOR! Closed containers may explode when exposed to extreme heat. Water spray

may be ineffective. Perforation of the pressurized container may cause bursting of the can. Isolate from heat, electrical equipment, sparks and open flame.

Special Firefighting Procedures: Evacuate area and fight fire from a safe distance.

Section 6 - Accidental Release Measures

Steps To Be Taken If Material Is Released Or Spilled: Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust.

Section 7 - Handling And Storage

Handling: Wash thoroughly after handling. Wash hands before eating. Use only in a well-ventilated area. Avoid breathing vapor or mist. Follow all MSDS/label precautions even after container is emptied because it may retain product residues.

Storage: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Do not store above 120 degrees F. Store large quantities in buildings designed and protected for storage of NFPA Class I flammable liquids. Contents under pressure. Do not expose to heat or store above 120 degrees F.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls: Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment.

Respiratory Protection: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

Skin Protection: Nitrile or Neoprene gloves may afford adequate skin protection. Use impervious gloves to prevent skin contact and absorption of this material through the skin.

Eye Protection: Use safety eyewear designed to protect against splash of liquids.

Other protective equipment: Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application.

Hygienic Practices: Wash thoroughly with soap and water before eating, drinking or smoking.

Section 9 - Physical And Chemical Properties

Boiling Range:
Odor:

-44 -420 F
Solvent Like

Vapor Density:
Odor Threshold:

Heavier than air
ND

| | | | |
|---------------------------------|--------|-------------------|-------------------|
| Appearance: | Liquid | Evaporation Rate: | Faster than Ether |
| Solubility in H ₂ O: | Slight | | |
| Freeze Point: | ND | Specific Gravity: | |
| Vapor Pressure: | | PH: | NE |
| Physical State: | Liquid | | |

(See section 16 for abbreviation legend)

Section 10 - Stability And Reactivity

Conditions To Avoid: Avoid all possible sources of ignition. Avoid temperatures above 120 degrees F.

Incompatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

Hazardous Decomposition: When heated to decomposition it emits acrid smoke and irritating fumes. By open flame, carbon monoxide and carbon dioxide.

Hazardous Polymerization: Will not occur under normal conditions.

Stability: This product is stable under normal storage conditions.

Section 11 - Toxicological Information

Product LD50: ND

Product LC50: ND

| Chemical Name | LD50 | LC50 |
|--------------------------|-----------------------------|--------------------------|
| Liquified Petroleum Gas | N.E. | N.E. |
| Acetone | N.D. | N.D. |
| Toluene | N.D. | N.D. |
| Xylene | N.D. | N.D. |
| Titanium Dioxide | >7500 mg/kg | N.D. |
| Magnesium Silicate | N.D. | TCLo:11mg/m3 inh. |
| Stoddard Solvents | N.D. | N.D. |
| Aliphatic Hydrocarbon | N.D. | N.D. |
| Propylene Carbonate | RAT 5620 ML/KG | RAT 1600PPM/8HR IHL |
| Ethylbenzene | 3500 mg/kg (ORAL, RAT) | N.D. |
| Barium Sulfate | N.D. | N.D. |
| Aromatic Hydrocarbon | N.D. | N.D. |
| Super High Flash Naphtha | 4700 MG/KG (ORAL, RAT) | 3670 MG/KG (INH, RAT) |
| Pigment Red 170 | <10000 mg/kg (ORAL, RAT) | N.D. |
| 1,2,4-Trimethylbenzene | N.D. | 18 g/m3 (RAT, 4 HR) |
| Pigment Black 7 | >8000 mg/kg (rat). | N.A. |
| Red Iron Oxide | N.D. | N.D. |
| Pigment Green 7 | >5000 mg/kg | N.D. |

| | | |
|-------------------|---------------------|------|
| Calcium Carbonate | (ORAL, RAT) N.D. | N.D. |
|-------------------|---------------------|------|

Section 12 - Ecological Information

Ecological Information: Product is a mixture of listed components.

Section 13 - Disposal Information

Disposal Information: Dispose of material in accordance to local, state and federal regulations and ordinances. Do not allow to enter storm drains or sewer systems.

Section 14 - Transportation Information

| | | | |
|---------------------------|---------|-------------------|-----|
| DOT Proper Shipping Name: | Aerosol | Packing Group: | — |
| DOT Technical Name: | — | Hazard Subclass: | 1 |
| DOT Hazard Class: | 2 | Resp. Guide Page: | 126 |
| DOT UN/NA Number: | UN 1950 | | |

Section 15 - Regulatory Information

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA "Hazard Categories" promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD, FIRE HAZARD

SARA Section 313:

Listed below are the substances (if any) contained in this product that are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

| Chemical Name | CAS Number |
|------------------------|-------------------|
| Toluene | 108-88-3 |
| Xylene | 1330-20-7 |
| Propylene Carbonate | 108-32-7 |
| Ethylbenzene | 100-41-4 |
| Aromatic Hydrocarbon | 64742-95-6 |
| 1,2,4-Trimethylbenzene | 95-63-6 |
| Pigment Green 7 | 1328-53-6 |

Toxic Substances Control Act:

Listed below are the substances (if any) contained in this product that are subject to the reporting requirements of TSCA 12(B) if exported from the United States:

None known

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

| <u>Chemical Name</u> | <u>CAS Number</u> |
|-----------------------------|--------------------------|
| Alkyd Resin Solution | 66070-60-8 |

Pennsylvania Right-to-Know:

The following non-hazardous ingredients are present in the product at greater than 3%.

| <u>Chemical Name</u> | <u>CAS Number</u> |
|-----------------------------|--------------------------|
| Alkyd Resin Solution | 66070-60-8 |
| ALKYD RESIN SOLUTION | 66070-60-8 |
| Yellow Iron Oxide | 51274-00-1 |

California Proposition 65:

Warning: The following ingredients present in the product are known to the state of California to cause Cancer.

| <u>Chemical Name</u> | <u>CAS Number</u> |
|-----------------------------|--------------------------|
| Microcrystalline Silica | 14808-60-7 |
| Propylene Oxide | 75-56-9 |
| Benzene | 71-43-2 |
| Lead Compounds | NOT SPECIFIED |
| Acetaldehyde | 75-07-0 |
| Beryllium Compounds | NOT SPECIFIED |
| Nickel Compounds | NOT SPECIFIED |
| Chromium Compounds | NOT SPECIFIED |
| Arsenic Compounds | NOT SPECIFIED |
| Cadmium Compounds | NOT SPECIFIED |
| Formaldehyde | 50-00-0 |

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

| <u>Chemical Name</u> | <u>CAS Number</u> |
|---------------------------------|--------------------------|
| Toluene | 108-88-3 |
| Benzene | 71-43-2 |
| Lead Compounds | NOT SPECIFIED |
| Ethylene Glycol Monoethyl Ether | 110-80-5 |
| Mercury Compounds | NOT SPECIFIED |
| Arsenic Compounds | NOT SPECIFIED |
| Cadmium Compounds | NOT SPECIFIED |

International Regulations: As follows -

CANADIAN WHMIS:

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

CANADIAN WHMIS CLASS: AB5 D2A D2B

Section 16 - Other Information

HMIS Ratings:

Health: 2*

Flammability: 4

Reactivity: 0

Personal Protection: X

VOLATILE ORGANIC COMPOUNDS, g/l: NA

REASON FOR REVISION:

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.