Printing date 01/03/2005

Finning date 01/03/2005		Reviewed off 01/03/2003		
1 Identification of substance				
Trade name:	SAFETY RED			
Product code:	0000200671			
Manufacturer/Supplier:	SET MOOR OF STC/ MORE			
	917 Crosby Avenue Sycamore, IL 60178			
	(815)-895-9101, www.seymourpaint.com			
Information department:	Health & Safety Department			
<b>Emergency information:</b>	CHEMTEL 1-800-255-3924, 813-248-0585 if located outside the U.S.			
2 Composition/Data on co				
Chemical Description:	This product is a mixture of the substances listed below with nonhazardo	bus additions.		
Dangerous components:64742-89-8VM&P Naptha		K Xn; R 20/22 19.07%		
74-98-6 propane		K       Xn; R 20/22       19.07%         K       F+; R 12       17.64%		
1317-65-3 Calcium Carbo	nate	<b>R</b> Xi; R 36/37/38 16.37%		
106-97-8 n-butane		<b>K</b> F+; R 12 10.36%		
64742-47-8 Mineral Spirits		<b>K</b> Xn, <b>K</b> F; R 11-65 4.72%		
Additional information:	For the wording of the listed risk phrases refer to section 3.			
<b>3 Hazards identification</b>				
Hazard description:	F+ Extremely flammable			
Physical dangers:	Warning! Pressurized container. Keep away from heat, sparks, and flame	<u>.</u>		
	R 12 Extremely flammable. Pressurized container: protect from sunlight and do not expose to ter	nperatures exceeding 50°C, i.e.		
	electric lights. Do not pierce or burn, even after use.			
Tenate of about town	Keep out of the reach of children.			
Effects of short-term overexposure:	Causes irritation to the eyes, nose, throat, skin, and central nervous s	system. Symptoms may include		
-	dizziness, throat irritation, headache, fatigue, swelling of eyes, and nausea	a.		
Effects of chronic	May cause permanent brain and nervous system damage. Repeated	overevrequire can also demoge		
overexposure:	kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberate	elv inhaling the contents may be		
	harmful or fatal.	,		
NFPA ratings (scale 0 - 4):	Health- 1 Flammability- 3			
	Reactivity- 3			
HMIS-ratings (scale 0 - 4):	Health= 1			
	Fire= 4 Physical Hazard= 3			
	Health- 1			
	Flammability- 3			
	Physical Hazard-3			
4 First aid measures				
After inhalation:	If breathing is difficult, administer oxygen.			
After skin contact:	Remove contaminated clothing. Wash exposed area with soap and water			
After eve contact:	Rinse opened eve for several minutes under running water. Then consult	a doctor.		
After swallowing:	Contact physician or poison control center.			
<b>5</b> Fire fighting measures				
Extinguishing agents:	CO2. sand, extinguishing powder, or water spray. Fight larger fires with	a water spray or alcohol resistant		
	foam.			
Protective equipment:	No special measures required.			
6 Assidentel velegge mangung				
6 Accidental release measures Personal safety				
precautions:	Wear protective equipment. Keep unprotected persons away.			
Environmental safety				
precautions:	Do not allow product to reach sewage systems or ground water.	(Contd. on page 2)		
		USA		

## Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 01/03/2005

Reviewed on 01/03/2005

Inform appropriate authorities in case of seepage into water course or sewage system.     Inform appropriate authorities in case of seepage into water course or sewage system.       Do not flush with water or aqueous cleansing agents. Use diluted caustic solution. Soak up spills v into absorbent material. Refer to section 15 for disposal information.       Handling and storage Fire/explosion protection:     Do not sunce. Protect from electrostic charges. Obscrve trossurtized container storage regulations. Consult with your local authorities. Bo not sunce. Protect from electrostic charges. Obscrve trossurtized container storage regulations. Consult with your local authorities. Bo not sunce. Protection:       Components with limit values that require monitoring at the workplace: 749-86 prognem     749-86 prognem       PEL     1800 mg/m, 1000 ppm TLV (4508) mg/m, 20200) ppm TLV (4508) mg/m, 20200 ppm TLV (4508) mg/m, 2020 mg/m, 2020 ppm TLV (4508) mg/m, 2020 mg/m,	ade name: SAFETY RED	
Measures for cleaning/ collecting:     Do not flush with water or aqueous cleansing agents. Use diluted caustic solution. Soak up spills v inert absorbent material. Refer to section 13 for disposal information.       Handling and storage     Do not smoke. Protect from electrostatic charges.       Storage requirements:     Do not smoke. Protect from electrostatic charges. Storage requirements:       Storage requirements:     Do not smoke. Protect from electrostatic charges. Keep away from sources of heat and direct sunlight. Do not warehouse in subfrezing conditions.       Storage requirements:     Storage requirements:       Storage requirements:     Do not smoke. Protection:       Components with limit values that require monitoring at the workplace:     74.98.6 propane       PTEL     1800 mg/m, 1000 ppm       Title (1800 mg/m, 1000 ppm     REE       Title (200 mg/m, 2000 ppm     REE       Title (200 mg/m, 800 ppm     REE       Title (200 mg/m, 800 ppm     REE       Title (200 mg/m, 800 ppm     REE       Title (		(Contd. of pa Inform appropriate authorities in case of seepage into water course or sewage system.
Handling and storage       Fire(explosion protection:     Do not spray on a naked flame or any incandescent material.       Do not spray on a naked flame or any incandescent material.     Do not spray on a naked flame or any incandescent material.       Storage requirements:     Observe messarized container storage requirations. Consult with your local authorities.       Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.       278-86 propine       PEL     1800 mg/m?, 1000 ppm       REL     1800 mg/m?, 1000 ppm       TLV (4508) mg/m?, 1020 ppm       General System and the storage requiration in the storage requiratin the storage requiration in the storage requir	Measures for cleaning/	
Storage requirements:     Do not smoke. Protect from electrostatic charges. Storage requirements:     Storage requirements:       Storage requirements:     Storage requirements:     Storage requirement:       Storage requirem	collecting:	Do not flush with water or aqueous cleansing agents. Use diluted caustic solution. Soak up spills v inert absorbent material. Refer to section 13 for disposal information.
Fire/explosion protection:     Do not snow. Protect from electrostatic charges. Observe prosection of heat and direct sunlight. Do not warehouse in subfreezing conditions. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.       Storage requirements:     Storage requirements:     Storage requirements:       Storage req	Handling and storage	
Storage requirements:       Observe messurized container storage regulations. Consult with your local authorities. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.         Stexposure controls and personal protection:       Components with limit values that require monitoring at the workplace:         74-98-6 propane       PEL         PEL       1800 mg/ms, 1000 ppm         REI.       1900 mg/ms, 200 ppm         Control dust       "Respirable fraction         REI.       1900 mg/ms, 200 ppm         General Information       Wash hands after use.         Breating equipment:       Use suitable respiratory protective device in case of insufficient ventilation.         Protective hygical       Math ands after use.         Breating equipment:       Use suitable respiratory protective device in case of insufficient ventilation.         Protective hygical       According to trade name description in section 1.         Goldright temperature:       Actional opages         Physical and chemical properties:         General Information:		
Components with limit values that require monitoring at the workplace:       74-98-6 prognae     74-98-6 prognae       PEL     1800 mg/m2, 1000 ppm       REL     1800 mg/m2, 1000 ppm       TV     (4508) mg/m2, 000 ppm       1317-65-3 Calcium Carbonate     70 all dust **Respirable fraction       REL     100: 57* mg/m2       **Total dust **Respirable fraction     70 all dust **Respirable fraction       REL     100 mg/m2, 800 ppm       Ch-97-8 n-butane     70 all dust **Respirable fraction       REL     100 mg/m2, 800 ppm       Ch-97-8 n-butane     70 all dust **Respirable fraction       TV     100 mg/m2, 800 ppm       Ch-97-8 n-butane     70 all dust **Respirable fraction       TV     100 mg/m2, 800 ppm       TAV     200 mg/m2       As total hydrocarbon vapor; Skin; (P)       Protective hydispir     70 all dust after use.       Breathing equipment:     Vash hands after use.       Vse protection of hands:     70 rotective glows. The glowe material has to be impermeable and resistant to the substance. No glo recommendation can be given.       Eye protection:     Tightly sealed goggles       Physical and chemical properties:     General Information: <t< td=""><td>Storage requirements:</td><td>Observe pressurized container storage regulations. Consult with your local authorities.</td></t<>	Storage requirements:	Observe pressurized container storage regulations. Consult with your local authorities.
74-98-6 propane       PEL     1800 mg/m <sup>2</sup> , 1000 ppm       PEL     1800 mg/m <sup>2</sup> , 1000 ppm       TIV     (4508) mg/m <sup>2</sup> , (2500) ppm       1317-65-2 Calcium Carbonate     PEL       PEL     15 <sup>+</sup> , 5 <sup>+</sup> mg/m <sup>2</sup> Total dust ***Respirable fraction     Total dust ***Respirable fraction       TIV     10 <sup>+</sup> , 5 <sup>++</sup> mg/m <sup>2</sup> *Total dust ***Respirable fraction     Total dust ***Respirable fraction       TLV     10 mg/m <sup>2</sup> , 800 ppm       Get     60       Otdays**     Wash hands after use.       Breathing equipment:     Use suitable respiratory protective device in case of insufficient ventilation.       Protective hygenic     Use suitable respiratory protective device in case of insufficient ventilation.       Breathing equipment:     Use suitable respiratory protective device in case of insufficient ventilation.       Frequencian     recommendation can be given.       Fy protection:     Tightly scaled goggles       Physical and chemical properties:     General Information:       Form:     Accoroling to trade name description in section 1.       Odor:     Solivent       Builing point/Boiling range:     -44°C (2°F)       Ignition temperature:     365.0°C (68°F)    <	Exposure controls and p	personal protection:
74-98-6 propane       PEL     1800 mg/m <sup>2</sup> , 1000 ppm       PEL     1800 mg/m <sup>2</sup> , 1000 ppm       TIV     (4508) mg/m <sup>2</sup> , (2500) ppm       1317-65-2 Calcium Carbonate     PEL       PEL     15 <sup>+</sup> , 5 <sup>+</sup> mg/m <sup>2</sup> Total dust ***Respirable fraction     Total dust ***Respirable fraction       TIV     10 <sup>+</sup> , 5 <sup>++</sup> mg/m <sup>2</sup> *Total dust ***Respirable fraction     Total dust ***Respirable fraction       TLV     10 mg/m <sup>2</sup> , 800 ppm       Get     60       Otdays**     Wash hands after use.       Breathing equipment:     Use suitable respiratory protective device in case of insufficient ventilation.       Protective hygenic     Use suitable respiratory protective device in case of insufficient ventilation.       Breathing equipment:     Use suitable respiratory protective device in case of insufficient ventilation.       Frequencian     recommendation can be given.       Fy protection:     Tightly scaled goggles       Physical and chemical properties:     General Information:       Form:     Accoroling to trade name description in section 1.       Odor:     Solivent       Builing point/Boiling range:     -44°C (2°F)       Ignition temperature:     365.0°C (68°F)    <	Components with limit val	lues that require monitoring at the workplace:
REL.     1800 mg/m <sup>2</sup> , 1000 ppm       1317-65-3 Calcium Carbonate       PTL     15*; 5** mg/m <sup>3</sup> "Total dust **Respirable fraction       PTL     15*; 5** mg/m <sup>3</sup> "Total dust **Respirable fraction       PTL     10*; 5** mg/m <sup>3</sup> "Total dust **Respirable fraction       PTOTAI       10 mg/m <sup>3</sup> 800 ppm       C4742-47*8 Mineral Spirits       TLV       1200 mg/m <sup>3</sup> As total hydrocarbon vapor: Skin; (P)       Protective hygionic       measures:     Wash hands after use.       Protective hygionic       measures:     Vast hands after use.       Protective hygionic     Protective gloves. The glove material has to be impermeable and resistant to the substance. No glu recommendation can be given.       Pytosical and chemical properties:     General Information:       Form:     Aerosol       Color:     According to trade name description in section 1. </td <td></td> <td></td>		
1317-65-3 Calcium Carbonate       PEL     15%: 5% mg/m <sup>3</sup> "Total dust **Respirable fraction       PTOTAI dust **Respirable fraction       110*: 5** mg/m <sup>3</sup> "Total dust **Respirable fraction       110*: 5** mg/m <sup>3</sup> "Total dust **Respirable fraction       110*: 5** mg/m <sup>3</sup> "Total dust **Respirable fraction       111       10 mg/m <sup>3</sup> REL       1900 mg/m <sup>3</sup> , 800 ppm       C4742-47-8 Mimeral Spirits       TLV       1900 mg/m <sup>3</sup> As total hydrocarbon vapor; Skin; (P)       Protective hygienic       measures:     Wash hands after use.       Breathing equipment:     Use suitable respiratory protective device in case of insufficient ventilation.       Protective hygienic     Protective gloves. The glove material has to be impermeable and resistant to the substance. No glu recommendation can be given.       Eye protection:     Tightly scaled goggles       Physical and chemical properties:     General Information:       Gorn:     Accoroling to trade name description in section 1.       Odor:     Solvent       Boiling point/Boiling range:     44°C (47°F)       Flash point:     -19°C (-2°F)	REL 1800 mg/m <sup>3</sup> , 1000 pp	m
PEL     15%: 5** mg/m³       *Total dust **Respirable fraction       10%: 5** mg/m³       **Total dust **Respirable fraction       10%: 5** mg/m³       **Total dust **Respirable fraction       10%: 5** mg/m³       **Total dust **Respirable fraction       10%: 00 mg/m³, 800 ppm       64742-47-8 Mineral Spirits       TLV     1200 mg/m³, 800 ppm       Fore     Use suitable respiratory protective device in case of insufficient ventilation.       Protection of hands:     Protective loyes.       Protection:     Tightly scaled goggles       Physical and chemical properties:     General Information:       Form:     Accrosol       Color:     According to trade name description in section 1.       Odor:     Solvent       Boiling point/Boiling	<b>.</b>	
**Total dust ***Respirable fraction       106-97-8 n-butane       FEL     1000 mg/m*, 800 ppm       64742-47-8 Mineral Spirits       TLV     1200 mg/m*, 800 ppm       64742-47-8 Mineral Spirits       TLV     200 mg/m*, 800 ppm       As total hydrocarbon vapor; Skin; (P)       Protective hygienic       measures:     Wash hands after use.       Breathing equipment:     Use suitable respiratory protective device in case of insufficient ventilation.       Protective layed goggles     Protective gloves. The glove material has to be impermeable and resistant to the substance. No gle recommendation can be given.       Eye protection:     Tightly saled goggles       Porter:     Accrosol       Color:     Stable at normal temperatures. Can may burst when exposed to temperatures exce		
Image: Second secon	*Total dust **Respira	ble fraction
TLV     10 mg/m3       (c)     106-97-8 n-butane       REL     1900 mg/m3, 800 ppm       TLV     1900 mg/m3, 800 ppm       64742-47-8 Mineral Spirits       TLV     1200 mg/m3, 800 ppm       64742-47-8 Mineral Spirits     Use suitable respiratory protective device in case of insufficient ventilation.       Protection     Trighty sealed goggles       Protection:     Tighty sealed goggles       Physical and chemical properties:     General Information:       General Information:     According to trade name description in section 1.       Odor:     According to trade name description in section 1.       Odor:     Solvent       Boiling point/Boiling range:     -44°C (-47°F)	KEL 10*; 5** mg/m <sup>3</sup>	hle fraction
REL 1900 mg/m <sup>3</sup> , 800 ppm 1900 mg/m <sup>3</sup> , 800 ppm     1900 mg/m <sup>3</sup> , 800 ppm       Get742-47-8 Mineral Spirits     TLV       TLV     200 mg/m <sup>3</sup> As total hydrocarbon vapor; Skin; (P)       Protective hygienic measures: Breathing equipment: Protection of hands: Protection of hands: Tightly sealed goggles     Wash hands after use. Breathing equipment: Protective gloves. The glove material has to be impermeable and resistant to the substance. No glaves the substance of the substance of the substance. No glaves the substance of the substance of the substance of the substance.       Pytestcal and chemical properties:     Color: Color: Boiling point/Boiling range: -44°C (-47°F)       Flash point:     -19°C (-2°F)       Ignition temperature:     365.0°C (689°F)       Auto igniting:     Product is not self-igniting. In use, may form flammable/explosive vapour-air mixture. In use, may form flammable/explosive vapour-air mixture. I	TLV 10 mg/m <sup>3</sup>	
TLV     1900 mg/m³, 800 ppm       64742-47-8 Mineral Spirits	106-97-8 n-butane	
TLV     200 mg/m³ As total hydrocarbon vapor; Skin; (P)       Protective hygienic measures: Breathing equipment: Protection of hands: Protective gloves. The glove material has to be impermeable and resistant to the substance. No gl recommendation can be given. Tightly sealed goggles       Physical and chemical properties: General Information: Form: Color: Odor: Boiling point/Boiling range: -44°C (-47°F)       Flash point: Boiling point/Boiling range: -19°C (-2°F)       Ignition temperature: Boger of explosion: Lower Explosion Limit: Upper Explosion Limit: Upper Explosion Limit: Density: Specific Gravity: Between 0.77 and 0.90 (Water equals 1.00)       VOC content: VOC content: VOC content: VOC content: VOC in weight percent (less acetone): 52.7 %	REL       1900 mg/m³, 800 ppm         TLV       1900 mg/m³, 800 ppm	1 1
As total hydrocarbon vapor; Skin; (P)       Protective hygienic measures:     Wash hands after use.       Breathing equipment:     Ves suitable respiratory protective device in case of insufficient ventilation.       Protection of hands:     Protective gloves. The glove material has to be impermeable and resistant to the substance. No glared measures:       Eye protection:     Tightly sealed goggles       Physical and chemical properties:     General Information:       General Information:     According to trade name description in section 1.       Color:     According to trade name description in section 1.       Odror:     Solvent       Boiling point/Boiling range:     -44°C (-47°F)       Flash point:     -19°C (-2°F)       Ignition temperature:     365.0°C (689°F)       Auto igniting:     Product is not self-igniting.       Danger of explosion Limit:     0.9 Vol %       Vapor Pressure:     40 PSI, 2750 hPa       Density:     Not determined.       Specific Gravity:     Between 0.77 and 0.90 (Water equals 1.00)       VOC content:     0.53 kg/l 4.40 lb/gl       VOC content:     0.53 kg/l 4.40 lb/gl       VOC content:     0.53 kg/l 4.40 lb/gl       VOC in weight percent (less actone):     5.7 % <td>64742-47-8 Mineral Spirits</td> <td>s</td>	64742-47-8 Mineral Spirits	s
Protective hygienic measures:     Wash hands after use.       Breathing equipment: Protection of hands:     Use suitable respiratory protective device in case of insufficient ventilation.       Protection of hands:     Protective gloves. The glove material has to be impermeable and resistant to the substance. No glue recommendation can be given.       Eye protection:     Tightly sealed goggles       9     Physical and chemical properties:       General Information:     Aerosol       Color:     According to trade name description in section 1.       Odor:     Solvent       Boiling point/Boiling range:     -44°C (-47°F)       Flash point:     -19°C (-2°F)       Ignition temperature:     365.0°C (689°F)       Auto igniting:     Product is not self-igniting.       Danger of explosion:     Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 1 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.       Lower Explosion Limit:     0.9 Vol %       Vapor Pressure:     40 PS1, 2750 hPa       Density:     Not determined. Sectific Gravity:       Between 0.77 and 0.90 (Water equals 1.00)     0.53 kg/1 / 4.40 lb/gl       VOC in weight percent (less acetone): 52.7 %       Water:     19.9 %		
measures:     Wash hands after use.       Breathing equipment:     Wash hands after use.       Protection of hands:     Use suitable respiratory protective device in case of insufficient ventilation.       Protection:     Tightly sealed goggles       9     Physical and chemical properties:       General Information:     Aerosol       Form:     Aerosol       Color:     According to trade name description in section 1.       Odor:     Solvent       Boiling point/Boiling range:     -44°C (-47°F)       Flash point:     -19°C (-2°F)       Ignition temperature:     365.0°C (689°F)       Auto igniting:     Product is not self-igniting.       Danger of explosion Limit:     0.9 Vol %       Uyper Explosion Limit:     0.9 Vol %       Vapor Pressure:     40 PSI, 2750 hPa       Density:     Not determined.       Specific Gravity:     Not determined.       Between 0.77 and 0.90 (Water equals 1.00)     VOC content:     0.53 kg/l / 4.40 lb/gl       VOC content:     0.53 kg/l / 4.40 lb/gl     Vol %       Water:     19.9 %		vapor; Skin; (P)
Breathing equipment: Protection of hands:     Use suitable respiratory protective device in case of insufficient ventilation. Protective gloves. The glove material has to be impermeable and resistant to the substance. No glar protection:       Eye protection:     Tightly sealed goggles       9 Physical and chemical properties:     Aerosol       General Information:     Aerosol       Form:     Aerosol       Color:     According to trade name description in section 1. Solvent       Boiling point/Boiling range:     -44°C (-47°F)       Flash point:     -19°C (-2°F)       Ignition temperature:     365.0°C (689°F)       Auto igniting:     Product is not self-igniting.       Danger of explosion Limit:     0.9 Vol %       Uyper Explosion Limit:     0.9 Vol %       Upper Explosion Limit:     0.9 Vol %       Ower Pressure:     Not determined.       Boults:     Not determined.       Between 0.77 and 0.90 (Water equals 1.00)     Ot determined.       Between 0.77 and 0.90 (Water equals 1.00)     Starp 1.44.00 ls/gl       VOC content:     0.53 kg/l / 4.40 ls/gl       Water:     19.9 %		Wash hands after use
recommendation can be given. Tightly sealed goggles     1       Pysical and chemical properties:       General Information:       Form:     Aerosol       Color:     According to trade name description in section 1. Solvent       Boiling point/Boiling range:     -44°C (-47°F)       Flash point:     -19°C (-2°F)       Ignition temperature:     365.0°C (689°F)       Auto igniting:     Product is not self-igniting.       Danger of explosion:     Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 1 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.       Lower Explosion Limit:     0.9 Vol %       Vapor Pressure:     40 PSI, 2750 hPa       Density:     Not determined. Between 0.77 and 0.90 (Water equals 1.00)       VOC content:     0.53 kg/1 / 4.40 lb/gl       VOC in weight percent (less acetome): 52.7 %     %	Breathing equipment:	Use suitable respiratory protective device in case of insufficient ventilation.
Eye protection:     Tightly sealed goggles       9 Physical and chemical properties:       General Information:       Form:     Aerosol       Color:     According to trade name description in section 1.       Odor:     Solvent       Boiling point/Boiling range:     -44°C (-47°F)       Flash point:     -19°C (-2°F)       Ignition temperature:     365.0°C (689°F)       Auto igniting:     Product is not self-igniting.       Danger of explosion:     Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 1 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.       Lower Explosion Limit:     0.9 Vol %       Vapor Pressure:     40 PSI, 2750 hPa       Density:     Not determined.       Specific Gravity:     Between 0.77 and 0.90 (Water equals 1.00)       VOC content:     0.53 kg/1 / 4.40 lb/gl       VOC in weight percent (less acetome): 52.7 %     52.7 %       Water:     19.9 %	Protection of hands:	Protective gloves. The glove material has to be impermeable and resistant to the substance. No glo
9 Physical and chemical properties:       General Information:       Form:     Aerosol       Color:     According to trade name description in section 1.       Odor:     Solvent       Boiling point/Boiling range:     -44°C (-47°F)       Flash point:     -19°C (-2°F)       Ignition temperature:     365.0°C (689°F)       Auto igniting:     Product is not self-igniting.       Danger of explosion:     Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 1 degrees fahrenheit.       Lower Explosion Limit:     0.9 Vol %       Upper Explosion Limit:     0.9 Vol %       Vapor Pressure:     40 PSI, 2750 hPa       Density:     Not determined.       Specific Gravity:     Between 0.77 and 0.90 (Water equals 1.00)       VOC content:     0.53 kg/l / 4.40 lb/gl       VOC in weight percent (less acetome): 52.7 %     9.9 %	Eve protection:	
General Information:     Aerosol       Form:     Aerosol       Color:     According to trade name description in section 1.       Odor:     Solvent       Boiling point/Boiling range:     -44°C (-47°F)       Flash point:     -19°C (-2°F)       Ignition temperature:     365.0°C (689°F)       Auto igniting:     Product is not self-igniting.       Danger of explosion:     Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 1 degrees fahrenheit.       In use, may form flammable/explosive vapour-air mixture.     0.9 Vol %       Upper Explosion Limit:     0.9 Vol %       Vapor Pressure:     40 PSI, 2750 hPa       Density:     Not determined.       Specific Gravity:     Between 0.77 and 0.90 (Water equals 1.00)       VOC content:     0.53 kg/l / 4.40 lb/gl       VOC in weight percent (less acetone): 52.7 %     Yeight for the section in the sec		
Form:AerosolColor:According to trade name description in section 1.Odor:SolventBoiling point/Boiling range:-44°C (-47°F)Flash point:-19°C (-2°F)Ignition temperature:365.0°C (689°F)Auto igniting:Product is not self-igniting.Danger of explosion:Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 1 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.Lower Explosion Limit:0.9 Vol % 40 PSI, 2750 hPaDensity: Specific Gravity:Not determined. Between 0.77 and 0.90 (Water equals 1.00)VOC content: VOC in weight percent (less acetone):0.53 kg/l / 4.40 lb/gl VOC in weight percent (less acetone):Vator9.9 %	· · ·	properties:
Color:According to trade name description in section 1.Odor:SolventBoiling point/Boiling range:-44°C (-47°F)Flash point:-19°C (-2°F)Ignition temperature:365.0°C (689°F)Auto igniting:Product is not self-igniting.Danger of explosion:Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 1 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.Lower Explosion Limit:0.9 Vol % 0.9 Vol %Vapor Pressure:40 PSI, 2750 hPaDensity: Specific Gravity:Not determined. Between 0.77 and 0.90 (Water equals 1.00)VOC content: WOC in weight percent (less acetone):0.53 kg/l / 4.40 lb/gl 9.9 %		
Odor: Boiling point/Boiling range:Solvent -44°C (-47°F)Flash point:-19°C (-2°F)Ignition temperature:365.0°C (689°F)Auto igniting:Product is not self-igniting.Danger of explosion:Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 1 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.Lower Explosion Limit:0.9 Vol % 40 PSI, 2750 hPaDensity: Specific Gravity:Not determined. Between 0.77 and 0.90 (Water equals 1.00)VOC content: VOC in weight percent (less acetome):0.53 kg/l / 4.40 lb/gl 19.9 %		
Boiling point/Boiling range:-44°C (-47°F)Flash point:-19°C (-2°F)Ignition temperature:365.0°C (689°F)Auto igniting:Product is not self-igniting.Danger of explosion:Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 1 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture. 0.9 Vol %Lower Explosion Limit:0.9 Vol % 40 PSI, 2750 hPaDensity: Specific Gravity:Not determined. Between 0.77 and 0.90 (Water equals 1.00)VOC content: WoC in weight percent (less acetome):0.53 kg/l / 4.40 lb/gl 9.9 %		
Ignition temperature:365.0°C (689°F)Auto igniting:Product is not self-igniting.Danger of explosion:Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 1 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.Lower Explosion Limit:0.9 Vol % 0.9 Vol %Upper Explosion Limit:0.9 Vol % 0.9 Vol %Density:Not determined. Between 0.77 and 0.90 (Water equals 1.00)VOC content:0.53 kg/l / 4.40 lb/gl VOC in weight percent (less acetone): 52.7 % 19.9 %		<b>ige:</b> $-44^{\circ}C(-47^{\circ}F)$
Ignition temperature:365.0°C (689°F)Auto igniting:Product is not self-igniting.Danger of explosion:Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 1 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.Lower Explosion Limit:0.9 Vol % 0.9 Vol %Upper Explosion Limit:0.9 Vol % 0.9 Vol %Density:Not determined. Between 0.77 and 0.90 (Water equals 1.00)VOC content:0.53 kg/l / 4.40 lb/gl VOC in weight percent (less acetone): 52.7 % 19.9 %	Flash point:	-19°C (-2°F)
Danger of explosion:     Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 1 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.       Lower Explosion Limit:     0.9 Vol %       Upper Explosion Limit:     10.9 Vol %       Vapor Pressure:     40 PSI, 2750 hPa       Density:     Not determined.       Specific Gravity:     Between 0.77 and 0.90 (Water equals 1.00)       VOC content:     0.53 kg/l / 4.40 lb/gl       VOC in weight percent (less acetone):     52.7 %       Water:     19.9 %		365.0°C (689°F)
degrees fahrenheit.     Image: Specific Gravity:       Lower Explosion Limit:     0.9 Vol %       Upper Explosion Limit:     10.9 Vol %       Vapor Pressure:     40 PSI, 2750 hPa       Density:     Not determined.       Specific Gravity:     Between 0.77 and 0.90 (Water equals 1.00)       VOC content:     0.53 kg/l / 4.40 lb/gl       VOC in weight percent (less acetone):     52.7 %       Water:     19.9 %	-Smuon comperature.	
degrees fahrenheit.     Image: Specific Gravity:       Lower Explosion Limit:     0.9 Vol %       Upper Explosion Limit:     10.9 Vol %       Vapor Pressure:     40 PSI, 2750 hPa       Density:     Not determined.       Specific Gravity:     Between 0.77 and 0.90 (Water equals 1.00)       VOC content:     0.53 kg/l / 4.40 lb/gl       VOC in weight percent (less acetone):     52.7 %       Water:     19.9 %	<u> </u>	
Lower Explosion Limit:0.9 Vol %Upper Explosion Limit:10.9 Vol %Vapor Pressure:40 PSI, 2750 hPaDensity:Not determined.Specific Gravity:Between 0.77 and 0.90 (Water equals 1.00)VOC content:0.53 kg/l / 4.40 lb/glVOC in weight percent (less acetone):52.7 %Water:19.9 %	Auto igniting:	Product is not self-igniting.
Upper Explosion Limit:10.9 Vol % 40 PSI, 2750 hPaDensity:Not determined. Between 0.77 and 0.90 (Water equals 1.00)VOC content:0.53 kg/l / 4.40 lb/gl 52.7 % Water:VOC in weight percent (less acetone):52.7 % 19.9 %	Auto igniting:	Product is not self-igniting. Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 1 degrees fahrenheit.
Vapor Pressure:40 PSI, 2750 hPaDensity:Not determined.Specific Gravity:Between 0.77 and 0.90 (Water equals 1.00)VOC content:0.53 kg/l / 4.40 lb/glVOC in weight percent (less acetone):52.7 %Water:19.9 %	Auto igniting: Danger of explosion:	Product is not self-igniting. Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 1 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.
Specific Gravity:Between 0.77 and 0.90 (Water equals 1.00)VOC content:0.53 kg/l / 4.40 lb/glVOC in weight percent (less acetone):52.7 %Water:19.9 %	Auto igniting: Danger of explosion: Lower Explosion Limit:	Product is not self-igniting. Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 1 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture. 0.9 Vol %
VOC content:0.53 kg/l / 4.40 lb/glVOC in weight percent (less acetone):52.7 %Water:19.9 %	Auto igniting: Danger of explosion: Lower Explosion Limit: Upper Explosion Limit:	Product is not self-igniting. Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 1 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture. 0.9 Vol % 10.9 Vol %
VOC in weight percent (less acetone): 52.7 % Water: 19.9 %	Auto igniting: Danger of explosion: Lower Explosion Limit: Upper Explosion Limit: Vapor Pressure: Density:	Product is not self-igniting.       Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 1 degrees fahrenheit.       In use, may form flammable/explosive vapour-air mixture.       0.9 Vol %       10.9 Vol %       40 PSI, 2750 hPa       Not determined.
Water: 19.9 %	Auto igniting: Danger of explosion: Lower Explosion Limit: Upper Explosion Limit: Vapor Pressure: Density:	Product is not self-igniting.       Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 1 degrees fahrenheit.       In use, may form flammable/explosive vapour-air mixture.       0.9 Vol %       10.9 Vol %       40 PSI, 2750 hPa       Not determined.       Between 0.77 and 0.90 (Water equals 1.00)
	Auto igniting:Danger of explosion:Lower Explosion Limit:Upper Explosion Limit:Vapor Pressure:Density:Specific Gravity:VOC content:	Product is not self-igniting.       Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 1 degrees fahrenheit.       In use, may form flammable/explosive vapour-air mixture.       0.9 Vol %       10.9 Vol %       40 PSI, 2750 hPa       Not determined.       Between 0.77 and 0.90 (Water equals 1.00)       0.53 kg/l / 4.40 lb/gl
(Contd. on pa	Auto igniting:Danger of explosion:Lower Explosion Limit:Upper Explosion Limit:Vapor Pressure:Density:Specific Gravity:VOC content:VOC in weight percent (le	Product is not self-igniting.       Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 1 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.       0.9 Vol %       10.9 Vol %       40 PSI, 2750 hPa       Not determined. Between 0.77 and 0.90 (Water equals 1.00)       0.53 kg/l / 4.40 lb/gl       ess acetone): 52.7 %

## Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 01/03/2005

Reviewed on 01/03/2005

Trade name: SAFETY RED		
	(Contd. of page 2)	
Solids content:	27.0 %	
<b>10 Stability and reactivity:</b>		
Conditions to be avoided:	Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.	
Possibility of Hazardous Reactions:	No dangerous reactions known.	
Ktactions.		
<b>11</b> Toxicological information	o <b>n:</b>	
Primary effect on the skin	: No irritant effect.	
Primary effect on the eye:	No irritating effect.	
Sensitization:	No sensitizing effects known.	
<b>12 Ecological information</b>		
Other information:	This product does not contain any chloroflourocarbons (cfc's), chlorinated solvents, or lead. No specific	
	ecological data is available for this product.	
Acquatic toxicity:	Harmful to aquatic organisms. Hazardous for water, do not empty into drains.	
<b>13 Disposal considerations</b>		
	spose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact.	
Partially empty cans cannot	be disposed of with regular trash. Do not heat or cut empty containers with electric or gas torches.	
Recommendation:	Empty cans should be recycled.	
14 Transport information:		
-		
Hazard class: Identification number:	2.1 N/A	
Label	2.1	
ADR/RID class:	2 5F Gases	
UN-Number: IMDG Class:	1950 2.1	
Packaging group:	П	
EMS Number:	F-D,S-U No	
Marine pollutant: ICAO/IATA Class:	2.1	
Propper shipping name:	Aerosols, Flammable	
	Consumer Commodity ORM-D	
15 Regulations		
	nely hazardous substances):	
None of the ingredients in the		
SARA Section 313 (Specifi		
None of the ingredients is list	sted.	
TSCA (Toxic Substances Control Act):	All ingredients are listed.	
	icals known to cause cancer:	
100-41-4 ethyl benzene		
PROPOSITION 65 Chemi	icals known to cause reproductive toxicity:	
None of the ingredients in the		
Canadian WHMIS:	Class A, B5Flammable Aerosols	
EPA:	A= Known human carcinogen B= Probable human carcinogen C= Possible human carcinogen	
	D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of	
	carcinogenicity (or no data is available).	
A= Known human carcinogen C= Possible human carcinogen		
D = Not classifiable as to hu	man carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).	
	(Contd. on page 4) USA	

Reviewed on 01/03/2005

Printing date 01/03/2005

## Trade name: SAFETY RED

	(Contd. of page 3)	
IARC:		
	is possibly carcinogenic to humans. There is limited evidence of carcinogenicity. s unclassifiable as to its carcinogenicity to humans.	
ACGIH TLVs:	A1-designates a confirmed human carcinogen.	
	A2-designates a suspected human carcinogen.	
	A3-designates an animal carcinogen.	
	A4-designates "not classifiable as a human carcinogen".	
A1-designates a confirmed	human carcinogen.	
A2-designates a suspected A3-designates an animal ca	human carcinogen.	
A3-designates an animal ca	arcinogen.	
A4-designates "not classifi	able as a human carcinogen".	
NIOSH:		
13463-67-7 titanium dioxi	ide	
USDA (United States		
Department of		
Agriculture):	This product was manufactured to conform to the USDA Food Safety and Inspection Service performance standards. These standards include, but are not limited to, the ability of this product to be safe for use in official meat and poultry establishments, and to perform well under a daily regimen of thorough cleaning, cyclical temperature change, and wet conditions.	
16 Other information		
This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.		
Contact:	Craig Swafford, Regulatory Affairs. Email: cswafford@seymourpaint.com	
Contact:	Craig Swarrord, Regulatory Analis. Email. cswarrord@seynourpaint.com	

USA