

MATERIAL SAFETY DATA SHEET



THE SHERWIN - WILLIAMS CO.
101 PROSPECT AVE. N.W.
CLEVELAND, OH 44115

EMERGENCY TELEPHONE NO.
(216) 566-2917
INFORMATION TELEPHONE NO.
(216) 566-2902

DATE OF PREPARATION
1 - Nov - 95

©1995, The Sherwin-Williams Co.

Alkyd Interior Finishes

A/3

					CLASSIC 990				WALL & WOOD	WALL & WOOD			
					SATIN	SEMI-GLOSS	368 VOC S/G	380 VOC S/G	EG-SHEL	PRIMER	PRIMER - VOC		
					Y13 W 2 Base X	A40 W 5 Base X A40 W 6 Base Y A40 W 7 Base Z	A40 W 15 Base X	A40 W 25 Base X A40 W 26 Midtone Base A40 W 27 Deeptone B	Y14 E 34 Base L Y14 Y 37 Base M Y14 Y 36 Base P Y14 A 31 Base R Y14 R 35 Base V Y14 R 33 Base W	B49 W 2 White	B49 W Z2 White		
SECTION II					ACGIH	OSHA							
CAS No.	HAZARDOUS INGREDIENT	(percent by weight)	TLV	PEL	Units	Vapor Pressure							
			<STEL>	<STEL>		(mm Hg)							
107-21-1	Ethylene Glycol		C 50	C 50	PPM	0.1	less than 5% may be added due to tinting						
64742-88-7	Mineral Spirits		100	100	Mg/M3	2.0	35	36-44	15	30-31	32-49	35	23
64742-88-7	Mineral Spirits 140-Flash					0.5							
14464-46-1	Cristobalite		0.05	0.05	Mg/M3	as Resp. Dust							3
14807-96-6	Talc		2	2	Mg/M3	as Resp. Dust	9	0-5		8-9	9-17	9	
12001-26-2	Mica		3	3	Mg/M3	as Resp. Dust						2	
471-34-1	Calcium Carbonate		10	15[5]	Mg/M3	as Dust Fraction	16	8-13	33	9-22		27	39
13463-67-7	Titanium Dioxide		10	10[5]	Mg/M3	as Dust Fraction	20	11-22	17	10-21	1-13	13	12
Weight per Gallon (lbs.)							10.76	8.86-9.99	11.83	10.41-10.63	8.19-9.36	11.09	12.02
Volatile Organic Compounds (VOC - lbs./gal.)							3.83	3.71-3.97	1.95	3.03-3.06	3.49-4.23	3.94	2.83
Photochemically Reactive							No	No	Yes	No	No	No	No
Flash Point (°F)							100	100	102	102	100	105	105
DOL Storage Category							2	2	2	2	2	2	2
Flammability Classification (Flammable - Combustible)							Combustible	Combustible	Combustible	Combustible	Combustible	Combustible	Combustible
HMIS (NFPA) Rating (health - flammability - reactivity)							2 2 0	2 2 0	2 2 0	2 2 0	2 2 0	2 2 0	2* 2 0

⁵ Ingredient subject to the reporting requirements of the Superfund Amendments and Reauthorization Act (SARA) Section 313, 40 CFR 372.65 C

→→→ MSDS Text Page Follows →→→

Section III - PHYSICAL DATA

PRODUCT WEIGHT - See TABLE	EVAPORATION RATE - Slower than Ether
SPECIFIC GRAVITY - 0.82-1.80	VAPOR DENSITY - Heavier than Air
BOILING RANGE - 300-416 °F	MELTING POINT - N.A.
VOLATILE VOLUME - 29-90 %	SOLUBILITY IN WATER - N.A.

Section IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION See TABLE FLASH POINT See TABLE LEL 1.0 UEL 7.0
See TABLE

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section V - HEALTH HAZARD DATA

ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

ACUTE Health Hazards

EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

EMERGENCY AND FIRST AID PROCEDURES

If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.
If on SKIN: Wash affected area thoroughly with soap and water.
Remove contaminated clothing and launder before re-use.
If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.
If SWALLOWED: Get medical attention.

CHRONIC Health Hazards

Crystalline Silica (Quartz, Cristobalite) is listed by IARC. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.

Ethylene Glycol is considered an animal teratogen. It has been shown to cause birth defects in rats and mice at high doses when given in drinking water or by gavage. There is no evidence to indicate it causes birth defects in humans.

Prolonged overexposure to solvent ingredients in Section II may cause adverse effects to the liver and urinary systems.

Rats exposed to titanium dioxide dust at 250 mg./m³ developed lung cancer, however, such exposure levels are not attainable in the workplace.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Section VI - REACTIVITY DATA

STABILITY - Stable

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION - Will Not Occur

Section VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Section VIII - PROTECTION INFORMATION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

These coating may contain materials classified as nuisance particulates (listed "as Dust" in Section II) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section II, the applicable limits for nuisance dusts are ACGIH TLV 10 mg./m³ (total dust), OSHA PEL 15 mg./m³ (total dust), 5 mg./m³ (respirable fraction).

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section II.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

Section IX - PRECAUTIONS

DOL STORAGE CATEGORY - See TABLE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep away from heat and open flame.
Consult NFPA Code. Use approved Bonding and Grounding procedures.
Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Section X - OTHER REGULATORY INFORMATION

CALIFORNIA PROPOSITION 65

WARNING: These products, except for A14Y2536, B33W200, and B34W2006, contain a chemical(s) known to the State of California to cause cancer.

This Material Safety Data Sheet conforms to the Hazard Communication standard, 29 CFR 1910.1200(g)(4), for similar complex mixtures.

The above information pertains to these products as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to these products may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.