

MATERIAL SAFETY DATA SHEET



THE SHERWIN - WILLIAMS CO.
101 PROSPECT AVE. N.W.
CLEVELAND, OH 44115

EMERGENCY TELEPHONE NO.
(216) 566-2917
INFORMATION TELEPHONE NO.
(216) 566-2902

DATE OF PREPARATION
1 - Nov - 95

©1995, The Sherwin-Williams Co.

PROMAR® 200 / 400 Latex Interior Finishes

LI/4

					PROMAR® 200				PROMAR® 400		
					FLAT	Eg-SHEL	SEMI-GLOSS	GLOSS	FLAT	Eg-SHEL	SEMI-GLOSS
	Base X	⇒	B30 W 201	B20 W 201	B31 W 201	B21 W 201	B30 W 401	B20 W 401	B31 W 401		
	Base Y	⇒	B30 W 202	B20 W 202	B31 W 202	B21 W 202	B30 W 402		B31 W 402		
	Base Z	⇒	B30 W 203	B20 W 203	B31 W 203	B21 W 203	B30 W 403		B31 W 403		
	Antique White	⇒	B30 W 204	B20 W 204	B31 W 204		B30 W 404	B20 W 404	B31 W 404		
	Navajo White	⇒	B30 W 205	B20 W 205	B31 W 205		B30 W 405		B31 W 405		
	Dover White	⇒	B30 W 206	B20 W 206	B31 W 206		B30 W 406	B20 W 406	B31 W 406		
			B30 W 207 Luminous	B20 W 207 Luminous	B31 W 207 Luminous	B21 W 207 Luminous	B30 B 400 Black				
			B28 W 200 Primer				B28 W 400 Primer				
SECTION II		HAZARDOUS INGREDIENT		ACGIH TLV	OSHA PEL	Units	Vapor Pressure				
		(percent by weight)		<STEL>	<STEL>		(mm Hg)				
107-21-1	Ethylene Glycol.	C 50	C 50	PPM	0.1		<2% added due to tinting	2-5	1-4	3-7	2-4 2-4 1-3
112-34-5	2-(2-Butoxyethoxy)-ethanol	Not Established			0.1			1-2	1-2	2-3	1 1-2
14808-60-7	Quartz	0.1	0.1	Mg/M3	as Resp. Dust		2-16 <except B30W207>				1-13
14464-46-1	Cristobalite	0.05	0.05	Mg/M3	as Resp. Dust		1 <B30W207 only>	0-0.1	0.0-0.1	0.0-0.1	0-3
1332-59-7	Kaolin	2	5	Mg/M3	as Resp. Dust		5-12 <except B30W207>	0-12			5-16 <except black>
14807-98-6	Talc	2	2	Mg/M3	as Resp. Dust		0-5				5 <primer only>
12001-26-2	Mica	3	3	Mg/M3	as Resp. Dust		0-3				
471-34-1	Calcium Carbonate.	10	15[5]	Mg/M3	as Dust [Resp. Fraction]		0-15	2-19	0.5-6		13 <black only> 10 0-6
13463-67-7	Titanium Dioxide.	10	10[5]	Mg/M3	as Dust [Resp. Fraction]		9-15	7-25	9-27	0-11	0-12 15 9-17
1333-86-4	Carbon Black.	3.5	3.5	Mg/M3	as Dust						2 <black only>
Weight per Gallon (lbs.)							10.18-12.25	10.31-11.71	9.53-10.89	9.41-11.04	9.59-11.29 10.29-10.30 9.53-9.63
Percent Water							40.3-54.6	37.2-51.9	40.3-55.7	38.6-50.7	49.5-69.2 54.0 55.0-55.7
Volatile Organic Compounds (VOC) - Total (lbs./gal.)							0.16-0.23	0.41-0.56	0.25-0.56	0.57-0.73	0.08-0.23 0.33 0.25-0.30
Volatile Organic Compounds (VOC) - Less Water (lbs./gal.)							0.40-0.73	1.13-1.22	0.72-1.18	1.32-1.57	0.40-0.64 0.99 0.72-0.86
HMIS (NFPA) Rating (health - flammability - reactivity)							1* 0 0	2 0 0	2 0 0	2 0 0	2* 0 0 2 0 0 2 0 0

§ Ingredient subject to the reporting requirements of the Superfund Amendments and Reauthorization Act (SARA) Section 313, 40 CFR 372.65 C

→→→ MSDS Text Page Follows →→→

Section III — PHYSICAL DATA

PRODUCT WEIGHT - See TABLE	EVAPORATION RATE - Slower than Ether
SPECIFIC GRAVITY - 1.12-1.55	VAPOR DENSITY - Heavier than Air
BOILING RANGE - 212-488 °F	MELTING POINT - N.A.
VOLATILE VOLUME - 57-81 %	SOLUBILITY IN WATER - N.A.
pH - 8.2-9.8	

Section IV — FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION FLASH POINT Not Applicable LEL N.Ap. UEL N.Ap.
Not Applicable

EXTINGUISHING MEDIA
Carbon Dioxide, Dry Chemical, Alcohol Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS
Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

SPECIAL FIRE FIGHTING PROCEDURES
Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section V — HEALTH HAZARD DATA

ROUTES OF EXPOSURE
Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

ACUTE Health Hazards
EFFECTS OF OVEREXPOSURE
Irritation of eyes, skin and upper respiratory system. In a confined area vapors in high concentration may cause headache, nausea or dizziness.

SIGNS AND SYMPTOMS OF OVEREXPOSURE
Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE
None generally recognized.

EMERGENCY AND FIRST AID PROCEDURES
If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.
If on SKIN: Wash affected area thoroughly with soap and water.
Remove contaminated clothing and launder before re-use.
If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.
If SWALLOWED: Get medical attention.

CHRONIC Health Hazards
Crystalline Silica (Quartz, Cristobalite) is listed by IARC. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.
Ethylene Glycol is considered an animal teratogen. It has been shown to cause birth defects in rats and mice at high doses when given in drinking water or by gavage. There is no evidence to indicate it causes birth defects in humans.
Prolonged overexposure to solvent ingredients in Section II may cause adverse effects to the liver and urinary systems.
Rats exposed to titanium dioxide dust at 250 mg./m³ developed lung cancer, however, such exposure levels are not attainable in the workplace.

Section VI — REACTIVITY DATA

STABILITY - Stable

CONDITIONS TO AVOID
None known.

INCOMPATIBILITY
None known.

HAZARDOUS DECOMPOSITION PRODUCTS
By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION - Will Not Occur

Section VII — SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
Remove all sources of ignition. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD
Waste from these products is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.
Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Section VIII — PROTECTION INFORMATION

PRECAUTIONS TO BE TAKEN IN USE
Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.
These coatings may contain materials classified as nuisance particulates (listed "as Dust" in Section II) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section II, the applicable limits for nuisance dusts are ACGIH TLV 10 mg./m³ (total dust), OSHA PEL 15 mg./m³ (total dust), 5 mg./m³ (respirable fraction).

VENTILATION
Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION
If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II.
When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES
Wear gloves which are recommended by glove supplier for protection against materials in Section II.

EYE PROTECTION
Wear safety spectacles with unperforated sideshields.

Section IX — PRECAUTIONS

DOL STORAGE CATEGORY - Not applicable

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

Section X — OTHER REGULATORY INFORMATION

CALIFORNIA PROPOSITION 65
WARNING: These products, except for A21W40, A21W89, A88W17, and B31W207, contain a chemical(s) known to the State of California to cause cancer.

This Material Safety Data Sheet conforms to the Hazard Communication standard, 29 CFR 1910.1200(g)(4), for similar complex mixtures.
The above information pertains to these products as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to these products may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.