

TRU-TEST MANUFACTURING CO -- 1538 HI-Q EPOXY SPRAY PAINT -- 8010-00F021116

=====
MSDS Safety Information
=====

FSC: 8010
MSDS Date: 07/25/1990
MSDS Num: BMLBQ
LIIN: 00F021116
Tech Review: 02/20/1992
Product ID: 1538 HI-Q EPOXY SPRAY PAINT
Responsible Party
Cage: TRUTE
Name: TRU-TEST MANUFACTURING CO
Address: 201 JANDUS
City: CARY IL 60013
Country: NK
Info Phone Number: (708) 639-5383
Emergency Phone Number: (800) 228-5635

=====
Preparer Co. when other than Responsible Party Co.
=====

Cage: TRUTE
Assigned Ind: N
Name: TRU-TEST MANUFACTURING CO
Address: 201 JANDUS RD
City: CARY IL 60013

=====
Contractor Summary
=====

Cage: TRUTE
Name: TRU-TEST MANUFACTURING CO
Address: 201 JANDUS RD
City: CARY IL 60013 US
Phone: 708-639-5383

=====
Ingredients
=====

Cas: 67-64-1
RTECS #: AL3150000
Name: ACETONE, DIMETHYL KETONE
% by Wt: 35%
OSHA PEL: 1000PPM
ACGIH TLV: 750PPM/1000STEL;9293
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS
Ozone Depleting Chemical: N

Cas: 64742-47-8
RTECS #: OA5504000
Name: KEROSENE (PETROLEUM), HYDROTREATED; PETROLEUM DISTILLATE,
HYDROTREATED
% by Wt: 4-8%
OSHA PEL: 500 PPM
ACGIH TLV: 100 PPM
Ozone Depleting Chemical: N

Cas: 64742-89-8
Name: LIGHT ALIPHATIC NAPHTHA, VM & P NAPHTHA
% by Wt: 8-12%
OSHA PEL: 200 PPM

ACGIH TLV: 100 PPM
Ozone Depleting Chemical: N

Cas: 108-88-3
RTECS #: XS5250000
Name: TOLUENE (SARA III)
% by Wt: 1-3%
Other REC Limits: 100 PPM
OSHA PEL: 200 PPM/150 STEL
ACGIH TLV: 50 PPM; 9293
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS
Ozone Depleting Chemical: N

Cas: 111-76-2
RTECS #: KJ8575000
Name: 2-BUTOXYETHANOL (ETHYLENEGLYCOL MONOBUTYL ETHER), BUTYL CELLOSOLVE,
BUTYL GLYCOL, GLYCOL ETHER EB
% by Wt: 1%
Other REC Limits: 25 PPM (SKIN)
OSHA PEL: S, 50 PPM
ACGIH TLV: S, 25 PPM; 9293
Ozone Depleting Chemical: N

Cas: 68476-86-8
Name: HYDROCARBON PROPELLANT, PETROLEUM GASES LIQUEFIED SWEETENED, C3-7
% by Wt: 25-30%
OSHA PEL: 1000 PPM
ACGIH TLV: 1000 PPM
Ozone Depleting Chemical: N

=====
Health Hazards Data
=====

Route Of Entry Inds - Inhalation: YES
Skin: YES
Ingestion: NO
Carcinogenicity Inds - NTP: NO
IARC: NO
OSHA: NO

Effects of Exposure: EYES: IRRITATION. SKIN: DRYNESS. INHALATION:
HEADACHE, DIZZINESS, NAUSEA, PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

Explanation Of Carcinogenicity: NONE

Signs And Symptions Of Overexposure: EYES: IRRITATION. SKIN: DRYNESS.
INHALATION: HEADACHE, DIZZINESS, NAUSEA, PERMANENT BRAIN & NERVOUS
SYSTEM DAMAGE.

First Aid: EYES: FLUSH W/FRESH WATER. SKIN: WASH W/SOAP & WATER.
INHALATION: REMOVE TO FRESH AIR. GIVE CPR OR OXYGEN IF NEEDED.
INGESTION: DON'T INDUCE VOMITING. KEEP PERSON WARM & QUIET. OBTAIN
MEDICAL ATTENTIO N IN ALL CASES.

=====
Handling and Disposal
=====

Spill Release Procedures: ELMINATE IGNITION SOURCES. CONTAIN SPILL, ABSORB
LIQUID W/CLAY, SAND OR FLOOR ABSORBENT. PREVENT RUN-OFF TO SEWERS,
STREAMS OR OTHER BODIES OF WATER.

Waste Disposal Methods: CONTAMINATED ABSORBENT MAY BE DEPOSITED IN A
LANDFILL IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS. DISPOSE OF
EMPTY CANS IN NON-INCINERATED TRASH ONLY. FLAMMABLE LIQUID.

Handling And Storage Precautions: ELMINATE IGNITION SOURCES. DON'T EXPOSE
OR STORE AT TEMPS >120F.

Other Precautions: DON'T TAKE INTERNALLY. AVOID SKIN CONTACT.

=====
Fire and Explosion Hazard Information
=====

Flash Point Text: <20F

Extinguishing Media: FOAM, CO2, WATER FOG & DRY CHEMICAL

Fire Fighting Procedures: TREAT AS A VOLATILE LIQUID FIRE. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERRED. CLOSE CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT.

Unusual Fire/Explosion Hazard: WATER MAY BE USED TO COOL FIRE EXPOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP/EXPLOSION & AUTO-IGNITION WHEN EXPOSED TO HEAT. FLAMMABLE LIQUID.

=====
Control Measures
=====

Respiratory Protection: USE NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IF >TLV. APPROVED MECHANICAL FILTER TO REMOVE SOLID AIRBORNE PARTICLES.

Ventilation: MECHANICAL/GENERAL/LOCAL EXHAUST

Protective Gloves: RECOMMENDED

Eye Protection: RECOMMENDED

Other Protective Equipment: IMPERVIOUS CLOTHING & BOOTS

Work Hygienic Practices: WASH HANDS BEFORE EATING, SMOKING OR USING BATHROOM. DON'T REUSE CONTAMINATED CLOTHING.

=====
Physical/Chemical Properties
=====

B.P. Text: <0F

Vapor Density: <AIR

Evaporation Rate & Reference: SLOWER THAN ETHER

Appearance and Odor: VARIES W/COLOR

Percent Volatiles by Volume: 85%

=====
Reactivity Data
=====

Stability Indicator: YES

Stability Condition To Avoid: HEAT, SPARKS, OPEN FLAMES & TEMPS ABOVE 120F

Materials To Avoid: STRONG OXIDIZING AGENTS

Hazardous Decomposition Products: CO2 & CO

Hazardous Polymerization Indicator: NO

=====
Toxicological Information
=====

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====
Regulatory Information
=====

=====
Other Information
=====

=====
HAZCOM Label
=====

Product ID: 1538 HI-Q EPOXY SPRAY PAINT

Cage: TRUTE

Company Name: TRU-TEST MANUFACTURING CO

Street: 201 JANDUS RD

City: CARY IL

Zipcode: 60013 US

Health Emergency Phone: 800) 228-5635

Date Of Label Review: 12/16/1998

Label Date: 12/16/1998

Hazard And Precautions: EYES: IRRITATION. SKIN: DRYNESS. INHALATION:
HEADACHE, DIZZINESS, NAUSEA, PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

EYES: IRRITATION. SKIN: DRYNESS. INHALATION: HEADACHE, DIZZINESS,
NAUSEA, PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

=====
Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of
Defense. The United States of America in no manner whatsoever expressly
or implied warrants, states, or intends said information to have any
application, use or viability by or to any person or persons outside the
Department of Defense nor any person or persons contracting with any
instrumentality of the United States of America and disclaims all
liability for such use. Any person utilizing this instruction who is not
a military or civilian employee of the United States of America should
seek competent professional advice to verify and assume responsibility
for the suitability of this information to their particular situation
regardless of similarity to a corresponding Department of Defense or
other government situation.