



172
turtle wax, inc
5655 West 73rd St.
Chicago, Illinois 60638-6211

Material Safety Data Sheet

TUR-C

EMERGENCY SPILL PHONE: 1 (800) 424-9300 (CHEMTREC) MSDS No: T-259R(C)
EMERGENCY MEDICAL PHONE: (Contact your local poison control center)
PRODUCT INFORMATION PHONE: 1 (708) 563-3600

NFPA Hazard Ratings: Health 1, Flammability 2, Reactivity 0
HMIS Hazard Ratings: Health 1, Flammability 2, Reactivity 0, Protection B

Prepared By: Research and Development, Phone: 1 (708) 563-3600
Date Issued: June 14, 1999

1 - MATERIAL IDENTIFICATION

PRODUCT NAME: **TURTLE WAX CARPET CLEANER AND PROTECTOR, T-259R(C)**

Chemical Family: Mixture: water, solvent, surfactants, additives.

Material Use or Occurrence: Carpet cleaner.

Product Identification No.: UN 1950 (Canada)

2 - IMPORTANT INGREDIENTS

CHEMICAL NAME (Synonyms)	CAS No.	PERCENT	PEL/TLV/TWA		CARCINOGEN (OSHA, NPT, IARC)
			OSHA	ACGIH	
Propylene Glycol Methyl Ether (Glycol Ether PM)	107-98-2	7-10%	100ppm	100ppm	No
Isobutane (Liquified Petroleum Gas)	75-28-5	3-5%	1000ppm	1000ppm	No

3 - CHEMICAL AND PHYSICAL PROPERTIES

Boiling Point: n/av
Specific Gravity: 1.010
Solubility In Water: Complete
Evaporation Rate: n/av
Coefficient of Oil/Water Distribution: n/av
Appearance and Odor: Hazy White translucent liquid with white foam. Odor: typical.

Melting Point: n/av
Vapor Pressure: 35 PSIG @ 70°F
Vapor Density (Air = 1): n/av
% Non-volatile: 8.0%
pH: 9.8

4 - FIRE AND EXPLOSION DATA

Flash Point (Seta Flash Cl. Cup): Sprayed vapors can be ignited with a flame. Flame length 14-16 inches, with no flash back to nozzle by CPSC test 16CFR 1500.3(b)(6)(viii); rated not flammable.
Explosive Limits: Lower: n/av Upper: n/av
Extinguishing Media: Water spray, Carbon Dioxide, Chemical Foam, Dry Chemical.
Special Fire Fighting Procedures and Hazards: Aerosol cans are under pressure, can explode when heated above about 140°F., and can become projectiles. Treat contents as flammable liquid/explosive vapor fire. Keep unignited containers cool with water. Vapors that are heavier than air, may collect in low areas, and may travel to distant source of ignition and flashback. Avoid flow of material into sewers. See Sec. 6 for personal protection.

5 - REACTIVITY INFORMATION

Stable: X Unstable: Precautions: None
Hazardous Polymerization Occurs: Does Not Occur: X
Incompatibility: Strong oxidizers such as peroxides.
Hazardous Decomposition Product: When burned: CO₂, CO, Hydrocarbons.

6 - HEALTH HAZARDS - PROTECTIVE MEASURES - FIRST AID

Inhalation:

- Repeated or excessive inhalation of vapor, mist or spray can cause irritation, chemical pneumonia, dizziness, and nausea. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal. No chronic effects known.
- Use NIOSH approved respirator appropriate for concentration of vapor or mist. Provide good ventilation.
- **Remove to fresh air.** Use artificial respiration and oxygen if needed.

Skin:

- Repeated or excessive contact can cause blisters or rash due to defatting action. No chronic effects known,
- Wear solvent resistant gloves and other clothing as needed to prevent exposure.
- **Remove contaminated clothing, and avoid ignition sources.** Wash effected areas thoroughly with soap and water.

Eyes:

- Causes irritation. No chronic effects known.
- Wear goggles. Have convenient eye wash stations.
- **Flush with water for 15 minutes.** Get medical attention if effects persist.

Ingestion:

- Causes digestive system upsets, dizziness, nausea, and may be fatal. If sucked into lungs, effects are same as for inhalation above. No chronic effects known.
- Avoid swallowing or sucking into lungs. Wear face shield if face contact is likely.
- **Rinse mouth. Do not induce vomiting.** Get prompt medical attention, especially if liquid is sucked into lungs.

IN ALL CASES: GET PROMPT MEDICAL ATTENTION IF EFFECTS PERSIST.

KEEP OUT OF REACH OF CHILDREN.

Most likely routes of entry: Skin, Eyes

7 - PRECAUTIONS FOR SAFE HANDLING AND USE

Spills and Leaks: Remove all ignition sources, and use spark proof equipment. Provide good ventilation. Take up spills with absorbent or by pumping and put into closed containers. Avoid flow to sewers. Floors may be slippery. See Section 6 for other protective measures.

Storage and Handling: Keep away from ignition or heat source. Store in cool and ventilated places, but avoid freezing. Keep containers closed.

Waste Disposal: In accordance with applicable local, state, and federal regulations.

Empty Containers: Do not cut or weld on empty containers before thoroughly cleaning. Rinse thoroughly before handling, reuse, or disposal.

8 - REGULATORY INFORMATION

DOT(HM-181) USA & Int'l:

For inner containers of less than 1 liter (33.8 ounces) each, less than 66 lb. total package weight, and not shipped by air:

Class and Label: ORM-D

Shipping description: None Required (May use "Consumer Commodity")

For inner containers of less than 1 liter each (33.8 ounces), over 66 lb. total package weight, or shipped by air:

Class and Label: 2.2 Non-flammable gas.

Shipping description: Aerosols, non-flammable (each not exceeding 1 L capacity), 2.2, UN1950.

SARA, Title III: Reportable for Section 313(Form R):

TSCA INVENTORY: All ingredients are commercially available and presumed to be listed by manufacturer.

CALIFORNIA PROP. 65: No listed substances are known to be present.

NEW JERSEY LABEL INGREDIENTS: Water (CAS# 7732-18-5), Sodium Lauryl Sulfate (CAS # 151-21-3), Propylene Glycol Methyl Ether (CAS # 107-98-2), Sodium Lauroyl Sarcosinate (CAS # 97-78-9), Isobutane (CAS # 75-28-5).

CANADA EPA DSL INVENTORY: Consult Turtle Wax, Inc. regarding status of ingredients.

EEC SIXTH AMENDMENT INVENTORY: Consult Turtle Wax, Inc. regarding status of ingredients.