

RF: 95MSDS42

Material Safety Data Sheet

Fox Valley Systems  
640 Industrial Drive  
Cary, Illinois 60013

Section I – Product Identification

Trade Name: Super Stripe Athletic Paint White  
Super Supreme Traffic Paint Unleaded Yellow  
White  
Super Stripe Traffic Paint White  
Unleaded Red  
Gray  
Blue  
Green  
Unleaded Yellow

Product Name: Mfg. Code ID: SSAW3R  
SSAW3D

TCW2R TCW2D  
TGY2R TGY2D  
TBE2R TBE2D  
TGN2R TGN2D  
TYU2R TYU2D  
STYU2R STYU2D  
STCW2R STCW2D  
TRU2R TRU2D

Product Purpose: Line/Stripe Marking

Appearance: Aerosol dispensing a paint. Color dependent upon grade. Characteristic odor.

Date Prepared: January 1, 2004

Emergency Telephone: Call Local Poison Control Center

Information Telephone: (847) 639-5744

. . . . .

Section II - Hazardous Ingredients

Ingredients	CAS NO	Percent By Weight	Threshold Limit Value OSHA	
			TWA PPM	STEL
Acetone	67-64-1	1-5	750	1000
2-Butoxyethanol	111-76-2	1-5	25*	NE
Butane	106-97-8	1-5	000	NE
Isobutane	75-28-5	15-20	NE	NE
Propane	74-98-6	5-15	1000	NE
Toluene (a)	108-88-3	10-20	100	150
VM & P Naphtha	64742-89-8	5-15	300	400
Xylene	1330-20-7	8-15	100	150
Ethylbenzene	100-41-4	2-3	100	125

Note: None of the above listed as a carcinogen in NTP, IARC, or OSHA 1910(z)

(a) Warning: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

\* Can be absorbed through the skin.

NE= Not Established

Volume Weight Average (TWA) – The employee’s average airborne exposure in any 8 hour work shift of a 40-hour workweek, which shall not be exceeded.

Short Term Exposure Limit (STEL) – The employee’s 15-minute time weighted average day exposure, which shall not be exceeded at any time during a workday.

Section III – Physical Characteristics

Evaporation Rate: Slower than ether

Vapor Density: Heavier than air

Percent Volatile By Volume: 70

Weight Per Gallon: 10 – 10.6 lbs.

Boiling Range: N/A

Specific Gravity: N/A

Vapor Pressure: N/A

Melting Point: N/A

#### Section IV – Fire and Explosion Hazard Data

Flammability Classification: Product Extremely Flammable

Level 2 Aerosol – NFPA 30B

Flash Point: -20F

Flammable Limits: LEL 1.9 UEL 8.5

Auto Ignition Temperature: N/A

Extinguishing Media: Foam, Carbon Dioxide, and Dry Chemical

Special Fire Fighting Procedures: Full protective equipment using self-breathing apparatus should be used. Water may be used to cool closed containers to prevent pressure build-up and possible explosion when exposed to extreme heat.

Unusual Fire and Explosion Hazards: Spray mist or vapors from can per 400 cubic feet of air may reach lower explosive limit and could be ignited by a flame or spark.

#### NFPA Rating

Type of Paint	Health	Flammability	Reactivity	
Unleaded	2	4	0	
Type of Paint	Health	Flammability	Reactivity	Personal Protection
Unleaded	2	4	0	0

- Key: 0 = Minimal Hazard  
1 = Slight Hazard  
2 = Moderate Hazard  
3 = Serious Hazard  
4 = Severe Hazard  
5 = Safety Goggles and Gloves

#### Section V - Health Hazard Data

### Effects of Overexposure

**Eyes:** May cause irritation, redness, tearing, blurred vision and conjunctivitis.

**Skin:** Prolonged or repeated contact may cause moderate irritation and defatting dermatitis.

**Breathing:** Excessive inhalation of vapors may cause headaches, nausea, drowsiness and irritation of mucous membranes of nose and throat.

**Ingestion:** May cause nausea.

### Emergency and First Aid Procedures

**In Eyes:** Flush with water for 15 minutes, lifting upper and lower lids occasionally, obtain medical attention.

**On Skin:** Wash contaminated area thoroughly with soap and water. Apply a moisturizing hand cream.

**If Breathed:** If affected, remove individual to fresh air. If breathing is difficult, administer oxygen only if trained. If breathing has stopped give artificial respiration, preferably mouth to mouth. Keep person warm, quiet and obtain medical attention.

**Other:** When using this product, do not eat drink or smoke.

**Note:** Following any first aid, medical advice should be obtained, especially if symptoms persist.

**If Swallowed:** Only induce vomiting at the instruction of a physician. Keep person warm, quiet and obtain medical attention.

**Threshold Value Limit:** See Section II

### Section VI -- Reactivity Data

**Stability:** Stable

**Conditions to Avoid:** Heat, Sparks and Fire.

**Materials to Avoid:** Strong oxidizing agents. Alkali and alkaline earth metals such as sodium, potassium and barium. Fine powders of light metals and their alloys such as magnesium.

**Hazardous Decomposition or Byproducts:** Thermal decomposition may yield Co or CO<sub>2</sub>.

Ventilation requirements vary with rate of product use. Supplement ventilation to keep below OSHA and ACGIH permissible levels of each ingredient.

Protective Gloves: Not applicable in normal use. Wear solvent resistant gloves where there is any risk of skin contact.

Eye Protection: Recommended

#### Section IX – Precautions to be Taken in Handling and Storing

Contents under pressure. Exposure to high temperatures may cause bursting. Avoid storing near radiator, stove open flame or direct sunlight. Do not incinerate or puncture can.

Do not spray into flames or any incandescant materials. Do not smoke while using this product or where solvent vapors are present.

DOT Storage Category: Do Not Store at Temperature Above 120°F.

#### Section 313 – Supplier Notification

These products contain the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372).

CAS#	Chemical Name	% By Weight Upper Bound Concentration
108-88-3	Toluene	30
1330-20-7	Xylene	8
100-41-4	Ethylbenzene	2

This information should be included in all MSDSs that are copied and distributed for these products.

This data sheet is not part of any contract of sale. The information contained herein is believed to be correct or is obtained from sources believed to be generally reliable. However, it is the responsibility of the user of these materials to investigate, understand and comply with the law and with procedures applicable to the safe handling and use of these materials. Fox Valley Systems, Inc. shall not be liable for any loss or damage directly or indirectly arising from the use of the product, and Fox Valley Systems, Inc. assumes no obligation or liability for reliance on the information contained herein, or omission herefrom.

CAS#	Chemical Name	% By Weight Upper Bound Concentration
67-64-1	Acetone	5
108-88-3	Toluene	20
1330-20-7	Xylene	15
100-41-4	Ethylbenzene	3

This information should be included in all MSDSs that are copied and distributed for these products.

This data sheet is not part of any contract of sale. The information contained herein is believed to be correct or is obtained from sources believed to be generally reliable. However, it is the responsibility of the user of these materials to investigate, understand and comply with the law and with procedures applicable to the safe handling and use of these materials. Fox Valley Systems, Inc. shall not be liable for any loss or damage directly or indirectly arising from the use of the product, and Fox Valley Systems, Inc. assumes no obligation or liability for reliance on the information contained herein, or omission herefrom.